



## 2nm dbl 360° Green, black anodized

200-015G2ST-B

2nm dbl 360° Green, black anodized  
Horizontal mounted with 0.75m cables

Specifications	
Number	200-015G2ST-B
Light Color	Green
Dimensions metric	Ø92,5mm x 68mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 2.7"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide
Materials	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
EAN	5704438022287
IP rating	IP68
UPC Code	879343022419
Connection	0.7m cable
Current consumption (mA @ 12VDC)	182
Current consumption (mA @ 24VDC)	176
Vessel size	Under 12M,12-20M,20-50M
Weight (Kg)	0 Kg

Specifications

<b>Weight (Oz)</b>	0.00 Oz
--------------------	---------