


SANI/FLEX Sanitation Hose



Elevate your boating with the ultimate sanitation solution. Trust our 10-year warranty for worry-free voyages. Unveil strength: Burst-resistant, 100 PSI rated, 15x odor-resistant. Defend against collapse from suction. Innovate with white butyl rubber, empowering flexibility—adventure with a vanilla-scented finish. Reimagine your voyage with the best marine hose.

Upgrade Your Boat's Hoses with SANI/FLEX The Undisputed Choice!

- Performance Beyond Compare: Trust in SANI/ FLEX's superior odor control, making it the gold standard for marine hose replacement, ensuring a pristine environment on board.
- Decade of Dependability: Navigate confidently knowing SANI/FLEX's 10-year warranty has your back against odor permeation for extended protection.
- Strength in Design: Revel in the unmatched resilience of double steel wire helix reinforcement and synthetic textile yarn, ensuring your hoses resist up to 100 PSI and outperform with 15x greater odor resistance.



EX ODOR SHIE

WARBA

00 PSI ISO 8099-2000

- Engineering Marvel: Step into the future of marine sanitation with SANI/FLEX's proprietary white butyl rubber compound, innovatively designed to seal off sewage odors and redefine industry benchmarks.
- Transformative Experience: Redefine ease and aesthetics in marine hoses with SANI/ FLEX's unmatched flexibility and the pleasing aroma of antibacterial vanilla, enhancing your boating adventure at every turn.

Raritan products are chosen by powerboat, sailboat, houseboat and RV owners and manufacturers the world over for their dependability, environmental responsibility, simplicity of installation, operation and maintenence. The product line includes house-hold style toilets, marine toilets, marine sanitation devices and systems, cleaning products, icemakers, water heaters and rudder angle indicators.

SANI/FLEX Sanitation Hose

Smooth, odor free, anti-bacterial butyl rubber, 15 times more effective than PVC hose for odor permeation, bends easily

> Double steel wire helix reinforcement

High strength synthetic textile yarn



Smooth fabric finish, white rubber resists abrasion, ozone, seawater and marine chemicals

Ordering							
Model	ID	OD	WT	Max Pressure	Burst Pressure	Max Vacumn	Bend Radius
SFH (By the foot)	1½"	1%"	0.6 lb / ft	105 psi	315 psi	13.5 psi	3.15"
SFH1 (By the foot)	1"	1%"	0.35 lb / ft	105 psi	315 psi	13.5 psi	1.97"
SFH50 (50' roll)	1½"	1%"	0.6 lb / ft	105 psi	315 psi	13.5 psi	3.15"
SFHC (100' roll)	1½"	1%"	0.35 lb / ft	105 psi	315 psi	13.5 psi	1.97"
SFH150 (50' roll)	1"	1%"	0.6 lb / ft	105 psi	315 psi	13.5 psi	3.15"



For more information contact: Raritan Engineering Company 530 Orange Street Millville, NJ 08332 E-Mail...... info@raritaneng.com Telephone:... 856-825-4900 Toll Free:..... 800-352-5630 Fax:...... 856-825-4409