



FATHOM II® LEVER DRAG 2-SPEED



- One-piece machined aluminum frame and sideplate for the ultimate in gear strength
- Dura-Drag™ system
- Stainless steel main and pinion gear
- Pull-to-turn preset knob eliminates accidental changes to the drag
- Forged and machined aluminum spool
- Quick-Shift II™ 2-speed system
- 5 stainless steel bearing system
- Removable top spacer bar and lugs (60 and 80 sizes only)



60N and 80 sizes include convertible lugs and top spacer bar which can be removed.

Model	Material #	Mono Cap. (yds/lb)	Braid Cap. (yds/lb)	Bearings	Max Drag @ Strike	Max Drag @ Full	Gear Ratio High/Low	Line Retrieve (in) High/Low	Weight (oz)
FTII10XNLD2	1563174	325 / 10	345/20	5	13 lbs	20 lbs	6.2:1 / 2.8:1	32 / 14	15.8
FTII15LD2	1563175	300 / 15	410/30	5	13 lbs	20 lbs	6.2:1 / 2.8:1	32 / 14	16.6
FTII15XNLD2	1563176	390 / 15	535/30	5	23 lbs	33 lbs	5.5:1 / 2.8:1	38 / 19	18.7
FTII15XNLD2LH	1563177	390 / 15	535/30	5	23 lbs	33 lbs	5.5:1 / 2.8:1	38 / 19	18.7
FTII25NLD2	1563178	300 / 25	555/40	5	23 lbs	33 lbs	5.5:1 / 2.8:1	38 / 19	20.1
FTII25NLD2LH	1563179	300 / 25	555/40	5	23 lbs	33 lbs	5.5:1 / 2.8:1	38 / 19	20.1
FTII30LD2	1563180	330 / 30	635/50	5	23 lbs	33 lbs	5.5:1 / 2.8:1	38 / 19	20.3
FTII30LD2LH	1563181	330 / 30	635/50	5	23 lbs	33 lbs	5.5:1 / 2.8:1	38 / 19	20.3
FTII40NLD2	1563182	315 / 40	355/65	5	23 lbs	40 lbs	6.0:1 / 1.9:1	50 / 16	24.1
FTII40NLD2LH	1563183	315 / 40	355/65	5	23 lbs	40 lbs	6.0:1 / 1.9:1	50 / 16	24.1
FTII60NLD2	1563184	300 / 60	700/100	5	23 lbs	50 lbs	5.1:1 / 1.6:1	50 / 16	32
FTII80LD2	1563185	300 / 80	815/130	5	23 lbs	50 lbs	4.2:1 / 1.6:1	41 / 16	32.9

• TOPSHOT capacities are located in the Master Capacity Chart.