




## FATHOM II® LEVER DRAG



- One-piece machined aluminum frame and sideplate for the ultimate in gear strength
- Dura-Drag™ system
- Stainless steel main and pinion gear
- Pull-To-Turn preset knob eliminates accidental changes to the drag

- Forged and machined aluminum spool
- 5 stainless steel bearing system
- Removable top spacer bar and lugs (60 size only)
- 40NHS and 60NHS have optimized drag progressions for billfish applications



### HIGHSPEED

HIGH SPEED MODELS  
AVAILABLE IN 40N AND 60N SIZES

Model	Material #	Mono Cap. (yds/lb)	Braid Cap. (yds/lb)	Bearings	Max Drag @ Strike	Max Drag @ Full	Gear Ratio High/Low	Line Retrieve (in)	Weight (oz)
FTHII10XNLD	1563376	325 / 10	345 / 20	5	13 lbs	20 lbs	5.3:1	27	14.1
FTHII15LD	1563377	300 / 15	410 / 30	5	13 lbs	20 lbs	5.3:1	27	15.3
FTHII25NLD	1563378	300 / 25	555 / 40	5	23 lbs	33 lbs	5.3:1	36	18.5
FTHII30LD	1563379	330 / 30	635 / 50	5	23 lbs	33 lbs	5.3:1	36	18.6
FTHII40NLDHS	1563380	600 / 20	1125 / 30	5	6 lbs	14 lbs	7.1:1	60	22.6
FTHII60NLDHS	1563381	590 / 30	1140 / 50	5	6 lbs	14 lbs	6.1:1	60	30.6

• TOPSHOT capacities are located in the Master Capacity Chart.