

SIKA TECHNOLOGY	COMPETITORS					
POLYURETHANE	BOATLIFE	зм	SIKA ADVANTAGES	SIKA APPLICATIONS		
Sikaflex®-290 DC	Teak Deck Sealant*	N/A	UV StableResistant to typical cleaning agents	■ Deck seam sealing		
Sikaflex®-291 LOT	Life Calk*	4200	■ Long open time (2-4) hours for projects that require slower product ■ Greater flexibility (+/- 25% joint movement) ■ Paintable/sandable ■ Adheres to self for easy repair ■ Easy to tool	 Thru-hull Keel joints Hatches Rub rails and vents 		
Sikaflex®-291	Life Calk*	4200 FS	■ 30-60 minute tack-free ■ Excellent sag resistance on large bead ■ Good above or below waterlline ■ Easy to tool	 Hull seams Bedding and sealing deck hardware 		
Sikaflex®-292	N/A	5200 & 5200 FS	 Non-sag for overhead or large vertical surfaces Clamping or fasteners often not needed Excellent green strength for initial bonding 30-minute tack-free Paintable/sandable 	 Deck-to-hull Stringers Struts and supports Transoms Radar mounts 		
Sikaflex®-295UV	Life Seal (Hybrid)	4000 UV**	 Permanently seals and bonds acrylic and polycarbonate Available in black or white for UV stable sealing Non-yellowing Easy to use 	■ General sealing of color-critical assemblies and components		
SILICONE	BOATLIFE	ЗМ	SIKA ADVANTAGES	SIKA APPLICATIONS		
Sikasil® N-Plus	Silicone Rubber	Marine Silicone	 Extremely long service life Excellent flexibility Available in clear and white Bonds to many substrates without primer 	 Window and door fabrication Conventional glazing Back bedding Cap, toe and heel beads Expansion and control joints Perimeter sealing of windows & doors Kitchen/bath solid surfaces Sanitary seals 		
2-COMPONENT MMA	BOATLIFE	зм	SIKA ADVANTAGES	SIKA APPLICATIONS		
SikaForce®-315	N/A	N/A	Very fast-settingPackaged for precise mixing and easy dispensing	■ Small-component bonding for glass, metals and most plastics		

^{*}Polysulfide **Polyether



SIKA TECHNOLOGY	COMPETITORS						
POLYESTER FILLERS	зм	BM EVERCOAT		ATC		SIKA ADVANTAGES	SIKA APPLICATIONS
SikaBiresin® AP077	Marine Premium Filler	I &		Polyfa	fair F26	 Suitable for above & below the waterline applications High heat-resistance of 400°F (209°C) Bonds to epoxy Styrene free 	 Gelcoat repair Blister repair Repair of damaged fiberglass parts
SikaBiresin® AP112	Marine High Strength Repair Filler	Kitty Hair & Everglass	3401	N/A		 Fiber-filled High impact strength Excellent heat and cold resistance Can be machined and tapped 	Structural repairsFRP, metal and wood bonding
EPOXY FAIRING COMPOUND	AWLGRIP	ALEXSI	ALEXSEAL			SIKA ADVANTAGES	SIKA APPLICATIONS
SikaBiresin® AP861 (A) SikaBiresin® AP861-1 (B)	D8200/D7200	Fairing Co	Fairing Compound 202			Smoother/creamier aspectLess pinholes	Fairing large dissimilar material surfaces such as aluminum, steel, FRP and wood
EPOXY RESIN SYSTEM	СОРОХУ*		WEST SYSTEMS*			SIKA ADVANTAGES	SIKA APPLICATIONS
SikaBiresin® CR72 (A)						 Higher physical properties* Higher thermal properties* 	 High performance marine boats, parts, and tooling applications Suitable for wet layup and vacuum-bagging
SikaBiresin® CH72-1 (B)	100A		WEST-105			Less brittle at room temp*Improved wet-out*	Suitable for wet layup and vacuum-bagging
SikaBiresin® CH72-2 (B)	4528A		VVE31-105				
SikaBiresin® CH72-3 (B)							