## **Rock Tamers RT240 LED System Instructions**

## **INCLUDES-**

- 2 WEATHER-PROOF SEALED RED LED TAIL LIGHT BARS
- 4 WIRE FLAT CONNECTOR & WIRING
- 12 STAINLESS STEEL CABLE TIES

## **INSTRUCTIONS-**

NOTE: ROCK TAMERS® TAIL LIGHT BARS ARE DESIGNED TO BE USED WITH THE ROCK TAMERS® MUDFLAP SYSTEM

- 1. WITH ROCK TAMERS® MUDFLAP SYSTEM INSTALLED ON THE VEHICLE, LOCATE THE FLAP CLAMP CARRIAGE BOLTS AND NUTS (SEE IMAGE 1)
- 2. LOOSEN ALL FLAP CLAMP NUTS AND PUSH THE CARRIAGE BOLTS AWAY FROM THE FLAP CLAMP (SEE IMAGE 2)
- 3. LOCATE THE THREADED PLUG ON ONE END OF THE TAIL LIGHT BAR, THIS WILL BE POSITIONED TO THE CENTER OF THE VEHICLE
- 4. STARTING FROM THE CENTER OF THE VEHICLE, SLIDE THE TAIL LIGHT BARS OVER THE FLAP CLAMP CARRIAGE BOLTS (SEE IMAGE 3)
  - \*NOTE: BOTH ROCK TAMERS® TAIL LIGHT BARS ARE THE SAME, THERE IS NO LEFT OR RIGHT
- 5. WHEN THE TAIL LIGHT BAR IS IN THE DESIRED LOCATION, TIGHTEN ALL FLAP CLAMP NUTS TO 30 IN-LB'S OF TORQUE
- 6. REPEAT STEPS 2 THRU 5 TO INSTALL THE OTHER TAIL LIGHT BAR ON THE OTHER SIDE OF THE ROCK TAMERS® MUDFLAP SYSTEM
- 7. LOCATE THE 4-WAY FLAT SOCKET ON YOUR VEHICLE
- 8. PLUG THE 4 WIRE FLAT CONNECTOR SECURELY INTO THE SOCKET ON THE VEHICLE
  \*NOTE: 2 WIRES COME OUT OF THE 4 WIRE CONNECTOR, A LEFT AND RIGHT. THE RIGHT-SIDE
  WIRE IS LONGER THAN THE LEFT WIRE
- 9. CONNECT THE RIGHT-SIDE WIRE TO THE RIGHT-SIDE OF THE TAIL LIGHT BAR, ROUTING THE WIRE AS DESIRED (SEE IMAGE 4)
  - \*NOTE: AFTER CONNECTING THE WIRE TO THE THREADED PLUG ON THE TAIL LIGHT BAR, FIRMLY TIGHTEN THE THREADED BARREL ON THE WIRE ONTO THE THREADED PLUG FOR A SECURE CONNECTION (SEE IMAGE 5)
- 10. CONNECT THE LEFT-SIDE WIRE TO THE LEFT-SIDE TAIL LIGHT BAR, ROUTING THE WIRE AS DESIRED (SEE IMAGE 4)
  - \*NOTE: AFTER CONNECTING THE WIRE TO THE THREADED PLUG ON THE TAIL LIGHT BAR, FIRMLY TIGHTEN THE THREADED BARREL ON THE WIRE ONTO THE THREADED PLUG FOR A SECURE CONNECTION (SEE IMAGE 5)
- 11. TEST THE ROCK TAMERS® TAIL LIGHT BARS BY CYCLING THROUGH RUNNING, BRAKE AND TURN SIGNALS
- 12. USE THE INCLUDED STAINLESS STEEL CABLE TIES TO SECURE THE WIRES AS DESIRED.

LEGAL DISCLAIMER: YOUR STATE/PROVINCE MAY PROHIBIT THIS PRODUCTS USE ON PUBLIC ROADS AND/OR RESTRICT ITS USE TO OFF-ROAD AREAS ONLY. THE MANUFACTURER AND RETAILER ASSUME NO RESPONSIBILITY FOR ANY USE OF THIS PRODUCT IN VIOLATION OF ANY APPLICABLE LAW