USER MANUAL QUICK START GUIDE **BM40AMPBT**



BLUETOOTH® ENABLED 2-WAY MARINE WAKETOWER SPEAKER SYSTEM



USER MANUAL

BM40AMPBT BLUETOOTH® ENABLED 2-WAY MARINE WAKETOWER SPEAKER SYSTEM



1016 VER:1.0 EN

BOSS Audio Systems 3451 Lunar Court • Oxnard, CA 93030 1-800-999-1236 US Toll-free 1-805-988-0192 US Local Main www.bossaudio.com Tech Support: www.b elC€[®]F©

1 3072 BM40AMPBT All Terrain Sound System lease read through these instructions carefully so you will know how to operate your model properly. After you have finished reading the instructions, keep this document in a safe place for future reference. THIS PACKAGE CONTAINS B_60 - BM40AMPBT Marine Waketower Speaker System (1 Active + 1 Passive) Ð - Bluetooth Multi-Function Controlle A10 - Handlebar Mounting Kit for Bluetooth Controlle - Rubber Pad EN Power Wire Harness Kit


Thank you for purchasing this

- User Manual Quick Start Guide / Poste

Bluetooth[®]

- Warranty Card

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks is under license. Other trademarks and trade names are those of their respective owners.



PAIRING & DISCOVERING A NEW BLUETOOTH CONNECTION 1) Power on the BM40AMPBT by pressing and holding down the Day/Pause multifunction

button for 3 seconds, the blue LEDs will start to flash, signalling that the BM40AMPBT is now ready for Bluetooth pairing.

NOTE: You have 30 Seconds before you must restart this procedure over again 2) Now that the BM40AMPBT is in pairing mode:

ANDROID users: a. Go into the Settings Menu of your device b. Enter the Bluetooth Menu c. TURN ON Bluetooth and press SCAN d. "BOOSS BM40AMPD" will now be displayed under AVAILABLE DEVICES e. Press "BOSS BM40AMPDT" to get Bluetooth connected

IOS users: a. Go into the Settlings Menu of your IOS device b. Enter the Bluetooth Menu c. TURN ON Bluetooth d. "BOSS BM40AMPBT" will now be displayed e. Press "BOSS BM40AMPBT" to get Bluetooth connected

9

GLOBAL M

PRINTED IN CHINA

3) If the BOSS BM40AMPBT is not seen, repeat the above steps to refresh the "Device List"

4) When the connection is successful, you are now ready to stream music from your favorite media player to the BM40AMPBT

To avoid potential shorts in the electrical system, be sure to disconnect the (-) batten/ cable before installation. Use this uni with a 12-Volt battery and negative group ing only. Failure to do so may result in a

When replacing ine luse, be sure to only use a luse or the raining speciated on this product avoid short-circuiting, cover any disconnected tasks with insulating tape. It is especially important to insulate any unused wires, which if the funcovered may cause specially important to insulate any unused wires, which if the funcovered to connect the pround use first. Ensure that the ground wire is properly connected to connect the ground wire first. Ensure that the ground wire is properly connected to metal parts of the vehicles body frame or direct to the battery if your vehicle does not have a grounded chassis frame. The ground wire of this unit power amp and a second powered system must be connected to the frame separately with and a second powered system must be connected to the name separately with different screws. If the screw for the ground wire loosens or falls out, it could result in fire or malfunction.



INFORMATION TO THE USER FCC COMPLIANCE STATEMENT

2

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions


(1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of this device.

This transmitter must not be co-located or operated in conjunction with any other antenna or transmitter. The Bluetooth antenna cannot be removed (or replaced) by antenna or transmitter. The Bluetodth antenna cannot be removed (rareplaced) by user. This equipment complex with FCC/1 (caliation exposure limits set forth for an uncontrolled environment and Creatos the FCC radio frequency (RF) Exposure (RJEs. This equipment has very low levels of Rf energy that it demend to comply without maximum premissive exposure (RFE) exposure (RFE) exposure (RJEs. This equipment has very low levels of Rf energy that it desirable that it should be installed and operative (RFE) evaluation. But it is desirable that it should be installed and operative the radiator at lease 32 0 on or more away from person's body (excluding extremities: hands, wrists, feet and ankles). Alteration or modifications carried out without appropriate authorization may invalidate the user's right to operate the equipment

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residen signed to provide reasonable protection against harmul interference in a residen-tial installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guar-antee that interference will not occur in a particular installation. If this equipment determined by turning the equipment of and on, the user is encouraged to try to correct the interference by one or more of the following measures: • Alexetence receivent the receiving automation. Relocate or reorient the receiving antenna.
 Increase the separation between the equipment and receiver.

Connect the equipment into an outlet on a circuit different from that to which the □ Consult the dealer or an experienced radio/TV technician for help.

CAUTION!! ADJUSTMENT OR ALTERATIONS OF THIS DEVICE MAY RESULT Â IN HAZARDOUS RADIATION EXPOSURE



RECONNECTION


1) Power on the BM40AMPBT and your last paired device Bluetooth


2) The unit will now automatically reconnect 3) If your device was previously paired with the BM40AMPBT, but it wasn't the last paired

a. Ensure no other devices are currently paired

b. Enter the *Bluetooth Menu* on your device being paired c. "BOSS BM40AMPBT" will display under AVAILABLE DEVICES d. Choose the "BOSS BM40AMPBT" to reconnect 4) If the device is out of range from the BM40AMPBT, it will disconnect automatically

a. To reconnect once device is back in range, press the UI Play/Pause





3

IMPORTANT SAFETY PRECAUTIONS

Do not operate mobile equipment while driving a motorized vehicle – safe driving and safety consideration of others should always be your highest priority.
In the everty us should not be mode, strange noises or oddr from this product, or any other abnormal signs, immediately turn of the power and consult your dealer or the nearest durbrized BOSA JUDIO Service Center. Using this product in this condition may result in permanent damage to the system.
Ease 1 concretionally without distortionality, then slowly increase the sound until you can also it to concretionly without distortion, or sar discontion.
BEUE TO OBSERVE THE FOLL OWING GUIDELLNES:
Don alt using the yolimes to be the distorted to the area what is around you. Do not turn up the volume so high that you can't hear what's around you.
 Use caution or temporarily discontinue use in potentially hazardous situations.

INSTALLATION PRECAUTIONS

WARNING - Always consult a professional installer

POARCINCS - Always consult a professional installation
Do not attempt to install or service this product by yourself. Installation or servicing of this
product by years without professional training and experience in electronic equipment
and motorized vehicle accessories may be dangerous and could expose you to the risk of
electric shock, injury or oright hazards
Refer any repairs to a qualified BOSS AUDIO SYSTEMS Service Center
The BMADAMPET To he powerder from a vehicle scigarette lighter *l* auxiliary power port, or
hard wired directly to the battery through an optional relay *l* accessory switch
When wind pricectly to the battery through an optional relay *l* accessory switch
When wind pricectly to the battery through an optional relay *l* accessory switch
The gmAdAmPET To has powerdured. It is suggested that an
optional fuse and fuse holder (not included) with minimum rating of 20 Amps be in line with
the positive battery terminal
The gmAdAMPET has a weather resistant design, it should not be submerged in or
under water under any circumstances
Use only the installation parts provided with the BM40AMPBT

CAUTION!! Using other mounting methods may void this warranty




MULTIFUNCTION CONTROLLER BLUETOOTH OPERATION

1) Press the DLAY/PAUSE once to start playing music or press the PLAY button from 2) To skip songs or advance, press the ONEXT TRACK button 3) To select the previous song, press the () PREVIOUS TRACK button

4) To raise the volume, *Press and Hold* the *VOL* + button 2 ~ 3 seconds 5) To lower the volume, *Press and Hold* the (i) *VOL* - button 2 ~ 3 seconds

Tips: Make sure your device Bluetooth volume is set at 75% level before stowing in to the carry pouch



GETTING TO KNOW YOUR BM40AMPBT MULTIFUNCTION CONTROLLER (MFC) 27811 (6) (1) 3 (4) (5)


GETTING S

MFC - MULTIFUNCTION CONTROLLER 2 BLUETOOTH INDICATOR LED(BLUE) / AUX-IN STATUS INDICATOR(RED)

- 3 3.5mm AUX-INPUT
- 4 PLAY/PAUSE / Press and hold for POWER ON

4

- PREVIOUS TRACK / Press and hold for VOL -5 6
- NEXT TRACK / Press and hold for VOL + / Warning tone while up to maximum volume Disconnect any paired Bluetooth device by pressing button for 4 seconds
- Clear any paired Bluetooth device in memory by pressing 🚯 button for 10 seconds
- for 10 seconds Disconnect any paired Bluetooth device by turning off bluetooth in your device setting menu
- When power on, blue back lit **()** button sparkles slowly for 30+ seconds to search for ex-paired device; after then **()** button blue back lit turns to sparkle quickly for 9mins 30secs until it is powered off 10
- When Bluetooth devie is out of connection range and Bluetooth pairing is disconnected automatically, and then blue back lit $\frac{3}{2}$ button sparkles slowly for 1 min to look for expaired device, after then $\frac{3}{2}$ button blue back lit turns to sparkle quickly for 9mins until it is powered off 11
- 12 When operation voltage is lower than 9.5Volt , MFC gives warning tone 13 MFC concludes tones of definition : Power On/Off, Bluetooth connection / Disconnection , Maximum volume, Lower voltage



MULTIFUNCTION CONTROLLER AUX-IN OPERATION

1) Power on the **BM40AMPBT** by pressing and holding down the UI PLAY/PAUSE multifunction button for 3 seco Disconnect any paired *Bluetooth* device by turning off *Bluetooth* in your devices Settings Menu Connect the integrated 3.5mm AUX-IN cable located on right side of the MFC to your devices headphone jac

VOLUME CONTROL

4) To raise the volume, Press and Hold the VOL + button 2 ~ 3 seconds 5) To lower the volume, Press and Hold the $(\begin{tabular}{c}\end{tabular})$ VOL - button 2 ~ 3 seconds

Tips: Make sure your device headphone volume is set at 75% level before stowing in to the carry pouch



BOSS AUDIO SYSTEM PHOTOS! WATCH FOR CONTEST GIVEAWAYS AND WIN PRIZES!

10

When replacing the fuse, be sure to only use a fuse of the rating specified on

fire or malfunction.

Tips: To avoid battery exhaustion, be sure to occasionally run the vehicles engine while using this product. Using this product without running the engine can drain the battery.

button once b. The **BM40AMPBT** will now reconnect to the device

VOLUME CONTROL