



3nm 360° Red, Ice-class, black anodized

300-114G2-PRO-I

3nm 360° Red, black anodized

Built-in De-icing function

Horizontally mounted on 400-037 alu base (IP68)

Cable direction side

incl. HDPE base plate

Quality cable glands - 3 sizes included:

9-17mm (3/8"-11/16") cable diameter

7-13mm (1/4"-1/2") cable diameter

4.5-10mm (5/32"-3/8") cable diameter

Specifications

Number 300-114G2-PRO-I

Light Color Red

Dimensions metric Ø92,5mm x 89,5mm

Certification This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under [Support](#)
 This Navigation Light conforms to USCG Commandant instructions M16672.2.
 Compliant to relevant sections of:
 - MIL-STD-461G
 - MIL-STD-901E
 - MIL-STD-167-1A
 - MIL-STD-1399/300-1

Intensity >15cd

Dimensions imperial Ø3.6" x 3.5"

Approved to COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR

Visibility 3nm

Operating temperature -60°C to 55°C

Mounting Horizontal

Materials Black hard coat anodized aluminum 50µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane

Operating Voltage 20-32VDC

EAN 5704438012448

IP rating IP68

Power draw (W) 2,9

UPC Code 879343012441

Connection Plug connector

Current consumption (mA @ 12VDC) 210

Specifications	
Stock status	Made to order
Current consumption (mA @ 24VDC)	120
Vessel size	Over 50M
Min. feed wire gauge	1.5mm ² AWG18
Weight (Kg)	1.14 Kg
Weight (Oz)	40.21 Oz