



2nm 360° Red, black w/FB base

201-014-FB-B

2nm 360° Red, black w/FB base

Horizontally mounted with 0.75m cable

Specifications

Number 201-014-FB-B

Light Color Red

Dimensions metric Ø92,5mm x 36mm

Certification This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under [Support](#)

Dimensions imperial Ø3.6" x 1.4"

Approved to COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR

Visibility 2nm

Included In Package 1 Navigation light,Installation guide,precabled with 0.75 meter shielded marine grade cable

Operating temperature -25°C to 55°C

Mounting Horizontal

Materials Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane

Operating Voltage 10-32VDC

EAN 5704438043015

IP rating IP68

Power draw (W) 2,1

UPC Code 879343043148

Connection 0.7m cable

Current consumption (mA @ 12VDC) 150

Specifications

Current consumption (mA @ 24VDC)	85
---	----

Vessel size	Under 12M,12-20M,20-50M
--------------------	-------------------------

Min. feed wire gauge	0.5mm ² AWG22
-----------------------------	--------------------------

Weight (Kg)	0 Kg
--------------------	------

Weight (Oz)	0.00 Oz
--------------------	---------