

SAFETY DATA SHEET

Effective Date: October 2022

ITEM: Inland Alert/Locate Kit

PART # 243 **UPC** 077403102433

CONTENTS

Marine Handheld Red Flare (HHRF) SDS

Marine Handheld Orange Smoke Signal (HHOS) SDS

Air Horn SDS

SHIPPING INFORMATION

UN0373, Signal devices, hand 1.4S (ERG 114) EX2019092055 EX1997080126



SAFETY DATA SHEET

1. Product and Company Identification

Marine Handheld Red Flare (HHRF)

Manufacturer's Information: Orion Safety Products

 3157 N 500 W
 EMERGENCY
 CHEMTREC

 Peru, Indiana 46970
 RESPONSE
 1-800-424-9300

 US 1-800-851-5260
 1-703-527-3887

Int'l (11) 1-765-472-4375

2. Hazards Identification

GHS Classifications Explosive Category 1.4
Skin Irritation Category 2

Eye Irritation Category 2

Eye Irritation Category 2A

STOT-Single Exposure Category 3

GHS Label Elements

Hazard Statements

H204 Fire or projection hazard
 H315 Causes skin irritation
 H319 Causes serious eye irritation
 H335 May cause respiratory irritation

Pictograms





Signal Word Warning

| Precautionary Statements | | P370 | In case of fire; use water deluge. |
|--------------------------|--|--------------|---|
| P102 | Keep out of reach of children. | P301/315 | IF SWALLOWED: Get immediate medical advice /attention. |
| P103 | Read carefully and follow all instructions | P302/352 | IF ON SKIN: Wash with plenty of soap and water. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. | P304/340/342 | IF INHALED: Remove victim to fresh air and keep at rest in a position |
| F210 | No smoking | | comfortable for breathing. If experiencing respiratory symptoms: Call a |
| P232 | Protect from moisture | | POISON CENTER or doctor/physician. |
| P261 | Avoid breathing dust/fumes. | P305/338/351 | IF IN EYES: Rinse cautiously with water for several minutes. Remove |
| P264 | Wash hands thoroughly after handling. | | contact lenses, if present and easy to do. Continue rinsing. |
| P270 | Do not eat, drink or smoke when using this product. | P332/313 | If skin irritation or rash occurs, get medical advice/attention. |
| P271 | Use only outdoors. | P501 | Dispose of contents / container in accordance with local and national |
| P280 | Wear protective eye protection. | | Regulations. |

Hazards Not Otherwise Classified (HNOC): produces hot flame

3. Composition / Information on Ingredients

| Component | CAS# | EINCS # | Percentage |
|--------------------|------------|-----------|------------|
| Strontium Nitrate | 10042-76-9 | 233-131-6 | <60% |
| Sulfur | 7704-34-9 | 231-722-6 | <25% |
| Potassium Nitrate | 7757-79-1 | 231-818-8 | <25% |
| Polyvinyl Chloride | 9002-86-2 | 200-831-0 | <5% |
| Paraffinic Oil | 64742-54-7 | 232-384-2 | <5% |
| Strontium Peroxide | 1314-18-7 | 215-224-6 | <2% |
| Potassium Chlorate | 3811-04-9 | 231-100-4 | <2% |

Note: Due to Confidential Business Information, "Trade Secrets", the exact percentage of each ingredient has not been disclosed. CBI information will be shared with appropriate authorities if circumstances warrant.

4. First Aid Measures

Description of first aid measures

Inhalation If contents are inhaled, remove to fresh air. Watch for signs of allergic reaction. If other symptoms develop, get medical aid immediately.

Skin If contents are contacted, wash with area with soap and water for 15 minutes. Remove contaminated clothing and wash before reuse. Get medical aid if irritation occurs.

Eyes If contents get into eyes, flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower lids. Remove contact lenses if easily possible. Get medical aid immediately.

Ingestion Get medical aid immediately.

Most important symptoms and effects both acuteand delayed Indication of any immediate medical attention and special treatment needed See section 2 labeling and section 11

No data available



5. Firefighting Measures

Extinguishing Media Water deluge Unsuitable Extinguishing Media Foam and dry chemical extinguishers and suffocation are ineffective.

Protective Equipment and Precautions for Firefighters

Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Prevent further propagation of fire by spraying unburnt

nearby product with water. Combat fire from a sheltered position.

nearby product with water. Combat fire from a sheltered position.

Specific Hazards Arising Only use outdoors. Flame and sparks are ejected out the open end of the flare when it functions. Do not point flare at any

from the Chemical part of the body or flammable material.

Further Information No data available

6. Accidental Release Measures

Personal Precautions / Protective Equipment / Emergency Procedures

Do not breathe smoke or contents. Avoid contact with skin and eyes. Wear flame retardant clothing with long sleeves, dust mask, rubber or nitrile gloves, safety goggles, safety shoes when cleaning up contents. Avoid friction on the released product. Keep away from ignition sources.

Environmental Precautions

Prevent dispersion of contents on soil and in water. Prevent contents from spreading or entering into drains, ditches, groundwater or rivers by using appropriate barriers.

Methods for Containment and Clean-up

Use caution when cleaning up spilled contents. Remove heat, flames, sparks and other sources of ignition. Use non-sparking tools and equipment. Prevent buildup of electrostatic charges by grounding. Clean spills in a manner that does not disperse dust into the air. When cleaning up contents, use local and/or general exhaust. Clean up avoiding dust generation and place in a well identified container. Do not absorb in sawdust or other combustible absorbents. Wash away remainder with plenty of water. Collect wash water for approved disposal.

7. Handling and Storage

Precautions for Safe Handling

Hold and point signal away from body when igniting. Hold signal downwind when burning. Avoid breathing smoke. Avoid contact with clothing and other combustible materials. Use outdoors only! Do not ignite or burn product inside a vehicle, boat cabin or building. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Avoid contact with skin and eyes. Avoid contact with heat, sparks, and flame. Signals should be allowed to burn to completion.

Conditions for Safe Storage, Including Any Incompatibilities

Store in a dry place away from direct sunlight, heat and incompatible materials. Store away from food and beverages. Store away from flammable materials, sources of heat, flame and sparks. Store at ambient temperature. Do not store partially burned signals in a vehicle, boat, closed container, warehouse, or any other building.

8. Exposure Controls / Personal Protection

Control Parameters

Exposure Limits OSHA PEL ACGIH TLV Strontium Nitrate Not established Not established Not established Not established Sulfur Potassium Nitrate Nuisance dust, 15 mg/m3 Nuisance dust, 15 mg/m³ No known hazardous components above No known hazardous components above Polyvinyl Chloride regulatory thresholds in this product regulatory thresholds in this product Paraffinic Oil 5 mg/m³ TWA 5 mg/m³ Strontium Peroxide 15 mg/m³ 15 mg/m³ Potassium Chlorate Not Established Not Established

Exposure Controls

Eye / Face Protection Safety glasses or goggles

Skin Protection None under normal conditions when using product unless prolonged handling is anticipated. Impervious protective

clothing, including gloves, boots, and a lab coat, apron or coveralls, as appropriate, when cleaning up spilled product.

Wash hands and face before eating, drinking or using tobaccoproducts

Respiratory Protection None under normal conditions when using product. A particulate respirator (NIOSH t N95 or better filters)

may be worn during the cleanup of spilled contents.

General Hygiene Use product outdoors away from combustible products. For cleanup of spilled contents, emergency showers and eye

wash stations should be available. Educate and train employees in the safe use and handling of hazardous materials. Maintain good housekeeping and safety practices. Do not let contents accumulate in storage or work areas. Clean

spills up promptly.



9. Physical and Chemical Properties

Appearance (color, physical form, shape): Grey powder

No data available Melting Point: No data available Solubility: No data available Boiling Point / Range: Freezing Point: Not applicable Not applicable **Evaporation Rate:** Not applicable Vapor Pressure: Not applicable Specific Gravity: Not applicable Vapor Density: Not applicable No data available Odor Threshold: No data available Flash Point: No data available Odor: Flammability: No data available Flammability Limits: No data available Relative Density: No data available Partition Coefficient: No data available Viscosity: No data available

Auto Ignition Temperature: No data available **Decomposition Temperature:** No data available

10. Stability and Reactivity

Chemical Stability: Stable Reactivity: No information available Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid Incompatible Materials **Hazardous Decomposition Products** Combustible materials, heat, Strong acids, strong fuels, ammonia salts and strong bases. Carbon monoxide, carbon dioxide, sulfur flames, sparks and other oxides and nitrogen oxides. sources of ignition. Moisture.

11. Toxicology Information

Ingredient acute toxicity information

Toxicology Oral LD50 Skin LD50 LC50 Strontium Nitrate Rat: 1892 mg/kg Not stated Not stated Rat:>2020 mg/kg Sulfur Rat: 5050 mg/kg Rat:>5.49 mg/L air concentration Potassium Nitrate Rat: 3750 mg/kg Not stated Not stated No known hazardous components No known hazardous components Polyvinyl Chloride Rat: >5000 mg/kg above regulatory thresholds above regulatory thresholds Paraffinic Oil Rat: >2000 mg/kg Rat: >2000 mg/kg No information found Strontium Peroxide Not Available Not Available Not Available Potassium Chlorate Rat 1870 mg/kg 2000 mg/kg (rabbit) No information found

Product toxicological information

Acute Toxicity Not classified - Acute Toxicity Estimate yields oral LD50 over 5000 mg/kg bw Skin Irritation / Corrosion Category 2 – over 10% of ingredients classified as a Category 2 skin irritant Category 2A – over 10% of ingredients classified as a Category 2A eye irritant Serious Eye Damage / Irritation Respiratory / Skin Sensitization Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Germ Cell Mutagen Not classified (Based on available data, the classification criteria are not met) Carcinogen Reproductive Toxicity Not classified (Based on available data, the classification criteria are not met)

STOT – single exposure Not classified (Based on available data, the classification criteria are not met) STOT - repeated exposure Category 3 - respiratory-over 10% of ingredients classified as a Category 3 respiratory STOT hazard

Aspiration Hazard Not classified (Based on available data, the classification criteria are not met)

Likely routes of exposure Skin, ingestion, inhalation

Symptoms related to the physical, Contents irritating to eyes due to chemical and physical properties of the mixture. Ingestion of chemical and toxicological characteristics contents may cause gastrointestinal irritation with nausea, vomiting and diarrhea. Individuals with known allergies to sulfide drugs may also have allergic reactions to elemental sulfur.

Delayed and immediate effects and chronic Inhalation of contents or smoke from burning flare will cause irritation to the lungs and mucus effects from short and long term exposure

membrane. Prolonged or repeated skin contact with contents may cause dermatitis.

Interactive effects No information found

12. Ecological Information

Ingredient toxicity / persistence / degradability / bioaccumulation / mobility in soil and water

Potassium Chlorate: fish: LC50 oncorhynchus mykiss (rainbow trout) 1750 mg/l – 96 hr, EC50 daphnia **Aquatic Toxicity**

magna (water flea) 1093 mg/l 24 hr

Strontium Nitrate: Acute toxicity - Fishes, Carassius auratus, LC100, 9,615 mg/l; Chronic toxicity - Fishes,

Gasterosteus aculeatus, LC100, 2.912 mg/l

Sulfur: Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) -> 180 mg/l - 96 h Toxicity to dapnia

and other aquatic invertebrates: EC50 – Daphnia magna (Water flea) - > 5,000 mg/l – 48 h

No information found Persistence / Degradability Bioaccumulation / Accumulation No information found

Strontium Nitrate: Water:: considerable solubility and mobility; Soil/sediments non-significant adsorption Mobility in Environmental Media

Other adverse effects No information found



13. Disposal Considerations (for spills and leakage)

Dispose of contaminated product and materials used in cleaning up spills or leaks in the manner approved for pyrotechnic material. Consult appropriate federal, state and local regulatory agencies to ascertain proper disposal procedures. Open burning is the preferred method of disposal for pyrotechnic materials. Allow flares to burn

14. Transportation Information

| | ID Number | Proper Shipping Name | Hazard Class | Packing Group | EX Number | Reportable Quantities | |
|-----------------------------|-----------|--|--------------|---------------|------------|-----------------------|--|
| Domestic & International | UN0373 | Signal devices, hand | 1.4S | n/a | 2019092055 | none | |
| Marine pollutant: n | 0 | Special precautions for user: no information available | | | | | |

15. Regulatory Information

| US Regulations | TSCA | CERCLA | CWA | CAA | SARA 313 | SARA 302 | Acute | Chronic | Fire | Reactivity | Pressure |
|--------------------|------------|--------|-----|--------|-------------|---------------------------------------|-----------|---------|--------|------------|----------|
| Strontium Nitrate | yes | no | no | no | yes | no | yes | no | no | yes | no |
| Sulfur | yes | no | no | no | no | no | yes | no | yes | no | no |
| Potassium Nitrate | yes | no | no | no | yes | no | no | no | no | yes | no |
| Polyvinyl Chloride | yes | no | no | no | no | no | yes | no | no | no | no |
| Paraffinic Oil | yes | no | no | no | no | no | no | no | no | no | no |
| Potassium Chlorate | yes | no | no | no | no | no | yes | no | no | yes | no |
| Strontium Peroxide | yes | no | no | no | no | no | yes | no | yes | yes | no |
| US States | Prop 65 | NJ | PA | Canada | ı | WHI | MIS | DLS | Europe | Wgk | |
| Strontium Nitrate | no | 1743 | no | | | C Oxidizing D1B Toxic D2B Toxic | materials | yes | | 2 | |

| Strontium Nitrate | no | 1743 | no | C Oxidizing materials D1B Toxic materials | yes | 2 |
|--------------------|----|------|-----|--|-----|------------|
| Sulfur | no | 1757 | yes | D2B Toxic materials B4 Flammable solid | yes | 1 / nwg |
| | | | • | D2B Toxic materials | • | • |
| Potassium Nitrate | no | 1574 | yes | C Oxidizing materials | yes | 1 |
| Polyvinyl Chloride | no | 3622 | no | No results | yes | not listed |
| Paraffinic Oil | no | 1437 | no | No results | yes | not listed |
| Potassium Chlorate | no | 1560 | yes | C Oxidizing materials D1B Toxic materials | yes | 2 |
| Strontium Peroxide | no | yes | no | C Oxidizing materials | yes | not listed |
| | | | | | | |

16. Other Information

| Revision Information: | March 2019 | Key / Legend |
|------------------------------|------------|--|
| | | HMIS: hazardous material identification system |

| NFPA Rating | | HMIS Rating | | | |
|--------------|---|-----------------|---|--|--|
| Flammability | 2 | Flammability | 1 | | |
| Health | 2 | Health | 3 | | |
| Reactivity | 1 | Physical Hazard | 1 | | |

NFPA: national fire protection association CAS: Chemical Abstracts Service number EINECS: European inventory of existing chemical substances OSHA PEL: occupational safety and health administration permissible exposure limit NIOSH TLV: national institute of occupational safety and health Threshold Limit Value NTP: National Toxicology Program

IARC: International Agency for Research on Cancer CWA: clean water act - US

TSCA: toxic substance control act - US CERCLA: comprehensive environmental response compensation and liability act - US CAA: clean air act - US SARA: superfund amendments and reauthorization act - US

PROP 65:California's Proposition 65 list WHMIS: workplace hazardous materials information system - Canada

DSL: Domestic Substances List - Canada WGK: water hazard classes - Germany

Legal Statement

This information is accurate to the best knowledge of Orion Safety Products. Orion Safety Products makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability or fitness for a particular purpose, with respect to the information set forth herein or the product to which the information refers. Accordingly, Orion Safety Products will not be responsible for damages resulting from use of or reliance upon this information. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.



SAFETY DATA SHEET

1. Product and Company Identification

Marine Hand Held Orange Smoke Signal (HHOS)

Identified Use: Emergency signal Use Advised Against: Do not use indoors or inside of a vehicle.

Manufacturers Information: Orion Safety Products

> 3157 N 500 W **EMERGENCY** CHEMTREC Peru, Indiana 46970 **RESPONSE** 1-800-424-9300 US 1-800-851-5260 1-703-527-3887 Int'l (11) 1-765-472-4375

> > H372

Regulations.

2. Hazards Identification

GHS Classifications

Category 1.4 H204 Explosive H315 Skin Irritation Category 2 Eye Irritation Category 2A H319 Skin Sensitization Category 1 H317 STOT-Repeated Exposure Category 1 H372

GHS Label Elements

P280

Pictograms Hazard Statements H204 Fire or projection hazard H315 Causes skin irritation H319 Causes serious eye irritation May cause an allergic skin reaction H317 Causes damage to lungs through

| | | | prolonged of repeated exposure |
|---------|--|--------------|---|
| Sig | nal Word Danger | | |
| Precaut | ionary Statements | P370 | In case of fire: use water deluge. |
| P102 | Keep out of reach of children. | P301/315 | IF SWALLOWED: Get immediate medical advice /attention. |
| P103 | Read carefully and follow all instructions. | P302/352 | IF ON SKIN: Wash with plenty of soap and water. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. | P304/340/342 | IF INHALED: Remove victim to fresh air and keep at rest in a position |
| FZ10 | No smoking | | comfortable for breathing. If experiencing respiratory symptoms: Call a |
| P232 | Protect from moisture | | POISON CENTER or doctor/physician. |
| P261 | Avoid breathing dust/fumes. | P305/338/351 | IF IN EYES: Rinse cautiously with water for several minutes. Remove |
| P264 | Wash hands thoroughly after handling. | | contact lenses, if present and easy to do. Continue rinsing. |
| P270 | Do not eat, drink or smoke when using this product. | P333/313 | If skin irritation or rash occurs, get medical advice/attention. |
| P271 | Use only outdoors. | P501 | Dispose of contents / container in accordance with local and national |

Hazards Not Otherwise Classified (HNOC): produces hot flame and copious amount of smoke

3. Composition / Information on Ingredients

Wear protective eye protection.

| <u> </u> | O | | |
|----------------------|------------|-----------|------------|
| Component | CAS# | EINCS # | Percentage |
| Solvent Yellow Dye | 842-07-9 | 212-668-2 | <40% |
| Lactose | 63-42-3 | 200-559-2 | <40% |
| Potassium Chlorate | 3811-04-9 | 231-100-4 | <25% |
| Solvent Orange 7 Dye | 3118-97-6 | 221-490-4 | <20% |
| Strontium Carbonate | 1633-05-2 | 216-643-7 | <1% |
| Calcium Carbonate | 1317-65-3 | 215-279-6 | <1% |
| Charcoal | 7440-44-0 | 231-153-3 | <1% |
| Umber | 12713-03-0 | 235-784-5 | <1% |
| Strontium Nitrate | 10042-76-9 | 233-131-9 | <1% |
| Shellac | 9000-59-3 | 232-549-9 | <1% |
| Potassium Nitrate | 7757-79-1 | 231-818-8 | <1% |
| Sawdust (cellulose) | 9004-34-6 | 232-674-9 | <1% |

Note: Due to Confidential Business Information, "Trade Secrets", the exact percentage of each ingredient has not been disclosed.

CBI information will be shared with appropriate authorities if circumstances warrant.

HHOS March 2019 1



4. First Aid Measures

Description of first aid measures

If contents are inhaled, remove to fresh air. Watch for signs of allergic reaction. If other symptoms develop, Inhalation

get medical aid immediately.

If contents are contacted, wash with area with soap and water for 15 minutes. Remove contaminated clothing Skin

and wash before reuse. Get medical aid if irritation occurs.

If contents get into eyes, flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower lids. Eyes

Remove contact lenses if easily possible. Get medical aid immediately.

Get medical aid immediately. Ingestion

Most important symptoms and effects both acute and delayed

Indication of any immediate medical attention and special treatment needed

See section 2 labeling and section 11

No Airborne Exposure Limits established

No information found

10 mg/m³

10 mg/m³

Nuisance dust 15 mg/m³.

No information found

No data available

5. Firefighting Measures

Foam and dry chemical extinguishers Extinguishing Media Water deluge Unsuitable Extinguishing Media and suffocation are ineffective.

Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated Protective Equipment and in the pressure demand or other positive pressure mode. Prevent further propagation of fire by spraying unburnt **Precautions for Firefighters**

nearby product with water. Combat fire from a sheltered position.

Only use outdoors. Contents / dust may form explosive mixtures. Flame and copious amounts of smoke are ejected Specific Hazards Arising from the Chemical out the open end of the signal when it functions. Do not point signal at any part of the body or flammable material.

Further Information No data available

6. Accidental Release Measures

Personal Precautions / Protective Equipment / Emergency Procedures

Do not breathe smoke or contents. Avoid contact with skin and eyes. Wear flame retardant clothing with long sleeves, dust mask, rubber or nitrile gloves, safety goggles, safety shoes when cleaning up contents. Avoid friction on the released product. Keep away from ignition sources. Contains strong dyes which will color all exposed areas.

Environmental Precautions

Prevent dispersion of contents on soil and in water. Prevent contents from spreading or entering into drains, ditches, groundwater or rivers by using appropriate barriers.

Methods for Containment and Clean-up

Use caution when cleaning up spilled contents. Remove heat, flames, sparks and other sources of ignition. Use non-sparking tools and equipment. Prevent buildup of electrostatic charges by grounding. Clean spills in a manner that does not disperse dust into the air. When cleaning up contents, use local and/or general exhaust. Clean up avoiding dust generation and place in a well identified container. Do not absorb in sawdust or other combustible absorbents. Mop up exposed area with bleach to destroy color. Wash away remainder with plenty of water. Collect wash water for approved disposal.

7. Handling and Storage

Precautions for Safe Handling

Hold and point signal away from body when igniting. Hold signal downwind when burning. Avoid breathing smoke. Avoid contact with clothing and other combustible materials. Use outdoors only! Do not ignite or burn product inside a vehicle, boat cabin or building. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Avoid contact with skin and eyes. Avoid contact with heat, sparks, and flame. Contains strong dyes which will color all exposed areas. Signals should be allowed to burn to completion. Unburned and partially burned signals should not be allowed to come into contact with surface and ground water.

Conditions for Safe Storage, Including Any Incompatibilities

Store in a dry place away from direct sunlight, heat and incompatible materials. Store away from food and beverages. Store away from flammable materials, sources of heat, flame and sparks. Store at ambient temperature. Do not store partially burned signals in a vehicle, boat, closed container, warehouse, or any other building.

8. Exposure Controls / Personal Protection

Control Parameters

Exposure Limits OSHA PEL ACGIH TLV Solvent Yellow Dye no information found none Nuisance particulate, 15 mg/m3 of total dust Nuisance particulate 10 mg/m³ of total dust Lactose

Potassium Chlorate No Airborne Exposure Limits established Solvent Orange 7 Dye No information found Strontium Carbonate 15 mg/m³ Calcium Carbonate 15 mg/m³ Charcoal Nuisance dust 15 mg/m³. Umber 30 mg/m³ Strontium Nitrate Not Established

Not Established Shellac 1000 ppm 1000 ppm

Nuisance dust 15 mg/m³. Potassium Nitrate Nuisance dust 15 mg/m³. Sawdust (cellulose) 5 mg/m³ 10 mg/m³

HHOS March 2019 2



Exposure Controls

Use product outdoors only! When cleaning up contents, use local and/or general exhaust. **Engineering Controls**

Eye / Face Protection Safety glasses or goggles

Skin Protection None under normal conditions when using product unless prolonged handling is anticipated. Contains strong dyes

which will color all exposed areas. When cleaning up spilled contents, wear full length impervious protective clothing, including gloves, boots, and a lab coat, apron or coveralls, as appropriate. Wash hands and face before eating,

drinking or using tobaccoproducts

None under normal conditions when using product. A particulate respirator (NIOSH t N95 or better filters) **Respiratory Protection**

may be worn during the cleanup of spilled contents.

Use product outdoors away from combustible products. For cleanup of spilled contents, emergency showers and eye wash stations should be available. Educate and train employees in the safe use and handling of hazardous materials.

Maintain good housekeeping and safety practices. Do not let contents accumulate in storage or work areas. Clean

spills up promptly.

9. Physical and Chemical Properties

General Hygiene

Appearance (color, physical form, shape):

Melting Point: Solubility: No data available No data available No data available pH: Boiling Point / Range: Not applicable Freezing Point: Not applicable **Evaporation Rate:** Not applicable Vapor Pressure: Not applicable Specific Gravity: Not applicable Vapor Density: Not applicable Odor: No data available Odor Threshold: No data available Flash Point: No data available Flammability Limits: Flammability: No data available No data available Relative Density: No data available

No data available

Partition Coefficient: No data available Viscosity:

Auto Ignition Temperature: >167°F **Decomposition Temperature:** No data available

10. Stability and Reactivity

Chemical Stability: Stable Reactivity: No information available Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid Incompatible Materials **Hazardous Decomposition Products** Excessive temperatures, Strong oxidizers, strong acids, oxidizing or reducing agents. Carbon monoxide, carbon dioxide, moisture, water, acids and Liquid acids of any kind. Hydrogen Fluoride, Ammonia Salts. nitrogen oxides.

11. Toxicology Information

ignition sources.

Ingredient acute toxicity information

| Toxicology | Oral LD50 | Skin LD50 | LC50 |
|----------------------|----------------------|-----------------------|----------------------|
| Solvent Yellow Dye | Rat: 5000 mg/kg | No information found | No information found |
| Lactose | Rat: 10000 mg/kg | No information found | No information found |
| Potassium Chlorate | Rat: 1870 mg/kg | 2000 mg/kg (Rabbit) | No information found |
| Solvent Orange 7 Dye | Rat: 5000 mg/kg | No information found | No information found |
| Strontium Carbonate | No information found | No information found | No information found |
| Calcium Carbonate | Rat 6450 mg/kg | Rabbit 500 mg/kg | No information found |
| Charcoal | Rat: > 15400 mg/kg | Rabbit: 3 g/kg | No information found |
| Umber | No information found | No information found | No information found |
| Strontium Nitrate | Rat: 2750 mg/kg | No information found | No information found |
| Shellac | Rat: 5000 mg/kg | No information found | No information found |
| Potassium Nitrate | Rat: 3750 mg/kg | No information found | No information found |
| Sawdust (cellulose) | Rat: > 5000 mg/kg | Rabbit: >2000 mg/kg | Rat 758 mg/m³ |
| | | | |

Product toxicological information

| Acute Toxicity | Not classified – Acute Toxicity Estimate yields oral LD50 over 5000 mg/kg bw |
|----------------------------------|---|
| Skin Irritation / Corrosion | Category 2 – over 10% of ingredients classified as a Category 2 skin irritant |
| Serious Eye Damage / Irritation | Category 2A – over 10% of ingredients classified as a Category 2A eye irritant |
| Respiratory / Skin Sensitization | Category 1 Skin – over 0.1% of ingredients are classified as a Category 1 skin. |

Germ Cell Mutagen Not classified (Based on available data, the classification criteria are not met)

Carcinogen Not classified (Based on available data, the classification criteria are not met) Reproductive Toxicity Not classified (Based on available data, the classification criteria are not met) STOT - single exposure Not classified (Based on available data, the classification criteria are not met) STOT - repeated exposure Category 1 – lungs over 1% of ingredients classified as a Category 1 STOT hazard Aspiration Hazard Not classified (Based on available data, the classification criteria are not met)

Likely routes of exposure Skin, ingestion, inhalation

Irritation to the eyes will cause watering and redness. Reddening, scaling, and itching are Symptoms related to the physical, chemical and toxicological characteristics characteristics of skin inflammation. Ingestion of contents may cause gastrointestinal irritation with nausea, vomiting and diarrhea. Inhalation will cause irritation to the lungs and mucus membrane.

Delayed and immediate effects and chronic effects from short and long term exposure

Both the solvent yellow and orange dyes may cause dermatitis in sensitive individuals

Interactive effects No information found

HHOS March 2019 3



12. Ecological Information

Ingredient toxicity / persistence / degradability / bioaccumulation / mobility in soil and water

Strontium Nitrate: Acute toxicity - Fishes, Carassius auratus, LC100, 9,615 mg/l; Chronic toxicity - Fishes,

Gasterosteus aculeatus, LC100, 2.912 mg/l

Aquatic Toxicity Potassium Chlorate: fish: LC50 oncorhynchus mykiss (rainbow trout) 1750 mg/l – 96 hr, EC50 daphnia

magna (water flea) 1093 mg/l 24 hr

Potassium Nitrate: fish: Guppy (Poecilia Reticulata) LC50 180 mg/L (96 h); zooplankton: Daphnia magna

LC50 490mg/l - 48hr

Persistence / Degradability Potassium Nitrate: Soluble in water Persistence is unlikely based on information available.

Bioaccumulation / Accumulation No information found

Mobility in Environmental Media

Strontium Nitrate: Water:: considerable solubility and mobility; Soil/sediments non-significant adsorption

Pateria in Nitrate: Will likely be mabile in the equipment due to its water colubility.

Potassium Nitrate: Will likely be mobile in the environment due to its water solubility.

Other adverse effects No information found

13. Disposal Considerations (for spills and leakage)

Flares should be allowed to burn to completion. Dispose of partially burned flares, ash, spilled contents, contaminated product and materials used in cleaning up spills or leaks in the manner approved for pyrotechnic material in accordance with federal, state and local requirements. Open burning is preferred method of disposal for pyrotechnic materials.

14. Transportation Information

| | ID Number | Proper Shipping Name | Hazard Class | Packing Group | EX Number | Reportable Quantities |
|-----------------------------|---|-------------------------|--------------|---------------|--------------|-----------------------|
| Domestic & International | UN0373 | Signal devices, hand | 1.4S | n/a | EX1997080126 | none |
| Marine pollutant: n | no Special precautions for user: no information available | | | | | |

15. Regulatory Information

| US Regulations | TS CA | CERCLA | CWA | CAA | SARA 313 | SARA 302 | Acute | Chronic | Fire | Reactivity | Pressure |
|---------------------|----------|--------|-----|-----|-------------|-------------|-------|---------|------|------------|----------|
| Solvent | V00 | no | no | no | VOC | no | VOC | V00 | no | no | no |
| Yellow Dye | yes | 110 | no | no | yes | 110 | yes | yes | no | no | no |
| Lactose | yes | no | no | no | no | no | no | no | no | no | no |
| Potassium Chlorate | yes | no | no | no | no | no | yes | no | no | yes | no |
| Solvent | yes | no | no | no | yes | no | no | yes | no | no | no |
| Orange 7 Dye | you | 110 | 110 | 110 | you | 110 | 110 | you | 110 | 110 | 110 |
| Strontium Carbonate | yes | | | | no | no | no | no | no | yes | no |
| Calcium Carbonate | yes | no | | | no | | no | no | no | yes | no |
| Charcoal | yes | no | no | no | no | no | no | no | no | no | no |
| Umber | yes | no | | | yes | | no | no | no | no | no |
| Strontium Nitrate | yes | no | no | no | no | no | yes | no | no | yes | no |
| Shellac | yes | no | no | no | no | no | no | no | no | no | no |
| Potassium Nitrate | yes | no | no | no | yes | no | no | no | no | yes | no |
| Sawdust (cellulose) | yes | no | no | no | no | no | no | no | no | no | no |

| Prop 65 | NJ | PA | Canada | WHMIS | DLS | Europe | Wgk |
|---------|--|---|--|---|--|---|---|
| yes | 0509 | yes | | D2A Very toxic materials D2B Toxic materials | yes | | not listed |
| no | no | no | | Non controlled | yes | | not listed |
| no | 1560 | yes | | C Oxidizing materials D1B Toxic materials | yes | | 2 |
| no | 0506 | yes | | D2B Toxic materials | yes | | 3 |
| no | no | | yes | No information found | | | nwg |
| no | | yes | yes | No information found | | | nwg |
| VAS | VAS | VAS | | D2A Very toxic materials | VAS | | nwg |
| yos | yes | yos | | D2B Toxic materials | ycs | | iwg |
| | yes | yes | yes | No information found | | | not listed |
| | | | | C Oxidizing materials | | | |
| no | 1743 | no | | | yes | | 2 |
| | | | | | | | |
| no | 0844 | yes | | No information found | | | not listed |
| no | 1574 | yes | | C Oxidizing materials | yes | | 1 |
| yes | no | no | | No results | yes | | not listed |
| | yes no no no no no yes | yes 0509 no no no 1560 no 0506 no no no yes yes yes no 1743 no 0844 no 1574 | yes 0509 yes no no no no 1560 yes no 0506 yes no no yes yes yes yes yes yes yes no 1743 no no 0844 yes no 1574 yes | yes 0509 yes no no no no 1560 yes no 0506 yes no no yes no yes yes yes yes yes yes yes yes no 1743 no no 0844 yes no 1574 yes | yes 0509 yes D2A Very toxic materials D2B Toxic materials D2B Toxic materials D2B Toxic materials D2B Toxic materials Non controlled C Oxidizing materials D1B Toxic materials D2B Toxic materials | yes 0509 yes D2A Very toxic materials yes no no no no Non controlled yes C Oxidizing materials yes no 0506 yes D2B Toxic materials yes no no no yes No information found no yes yes No information found D2A Very toxic materials yes yes yes yes No information found D2B Toxic materials yes D2B Toxic materials yes no no 1743 no D1B Toxic materials yes D2B Toxic materials yes No information found C Oxidizing materials yes D2B Toxic materials yes | yes 0509 yes D2A Very toxic materials yes no no no no Non controlled yes C Oxidizing materials yes D1560 yes D2B Toxic materials yes D1560 yes D2B Toxic materials yes D2B Toxic materials yes No information found no yes yes No information found D2A Very toxic materials yes yes yes yes D2B Toxic materials yes No information found C Oxidizing materials yes D2B Toxic materials yes |

HHOS March 2019 4



16. Other Information

Revision Information: March 2019

NFPA RatingHMIS RatingFlammability2Flammability1Health2Health3Reactivity1Physical Hazard1

Key / Legend

HMIS: hazardous material identification system NFPA: national fire protection association CAS: Chemical Abstracts Service number

EINECS: European inventory of existing chemical substances

OSHA PEL: occupational safety and health administration permissible exposure limit

NIOSH TLV: national institute of occupational safety

and health Threshold Limit Value NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

CWA: clean water act - US

TSCA: toxic substance control act - US CERCLA: comprehensive environmental response

compensation and liability act – US

CAA: clean air act - US

SARA: superfund amendments and reauthorization

act - US

PROP 65:California's Proposition 65 list WHMIS: workplace hazardous materials

information system - Canada

DSL: Domestic Substances List - Canada WGK: water hazard classes - Germany

Legal Statement

This information is accurate to the best knowledge of Orion Safety Products. Orion Safety Products makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability or fitness for a particular purpose, with respect to the information set forth herein or the product to which the information refers. Accordingly, Orion Safety Products will not be responsible for damages resulting from use of or reliance upon this information. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation

HHOS March 2019 5



Safety Data Sheet

Orion Safety Signal Horn

Section 1. Identification

Product Identifier Orion Safety Signal Horn

Synonyms 507, 507R, 508, 508R, 509, 509R, 510, 510R

Manufacturer Stock N/A

Numbers

Personal Safety - Hand held signaling device. Prior to use, read all label instuctions and warnings.

Uses advised against Use Only as Directed - Read label instructions carefully. Keep out of reach of

children. Intentional misuse by deliberately concentrating and/or inhaling contents

may be fatal.

Manufacturer Contact

Recommended use

Address Falcon Safety Products, Inc.

25 ImClone Drive Branchburg, NJ, 08876

USA

Phone **Emergency Phone** Fax (908) 707-4900 (800) 498-7192 N/A

Section 2. Hazards Identification

FLAMMABLE AEROSOLS - Category 2 Classification

N/A

GASES UNDER PRESSURE - Compressed gas

Signal Word Warning

Pictogram



Hazard Statements Precautionary Statements

Response N/A

Prevention Do not spray on an open flame or other ignition source. Keep away from heat.

Pressurized container: Do not pierce or burn, even after use.

Do not store in enclosed vehicle. Storage

Protect from sunlight. Store in a well-ventilated place.

Store at temperatures not exceeding 120 degrees F/49 degrees C

Disposal N/A

General Keep out of reach of children

Ingredients of unknown

toxicity

0%

Hazards not Otherwise

Classified

N/A

No Data Available

Section 3. Ingredients

| CAS | Ingredient Name | Weight % |
|---------|-----------------------|----------|
| 75-37-6 | Ethane, 1,1-difluoro- | 100 % |

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Never give anything by mouth to an unconscious person. When symptoms General Advice

persist or in all cases of doubt, seek medical advice.

Inhalation Remove from exposure, lie down. Move to fresh air. Keep patient warm and at

rest. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. Get immediate medical attention.

Skin Take off all contaminated clothing immediately. Flush area with lukewarm water.

Do not use hot water. If frostbite has occurred, call a physician.

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get Eye

medical attention.

Ingestion Is not considered a potential route of exposure.

Most important

delayed

Anaesthetic effects: light-headedness, irregular heartbeat with a strange symptoms/effects, acute and sensation in the chest, heart thumping, apprehension, feeling of fainting,

dizziness or weakness.

Protection of First-aiders If potential for exposure exists refer to Section 8 for specific personal protective

equipment.

Notes to Physician Because of possible disturbances of cardiac rhythm catecholamine drugs, such

as epinephrine, which may be used in situations of emergency life support,

should be used with special caution.

Section 5. Fire Fighting Measures

Suitable Extinguishing

Media

Unsuitable Extinguishing

Media

Specific Hazards

Water spray, water fog, dry chemical, alcohol resistant foam, carbon dioxide

(CO2)

No applicable data available.

Flammable. This substance's fire decomposition by-products will include hydrofluoric acid and possibly carbonyl flouride. Avoid contact with these materials, which are toxic and irritating. Evacuate personnel immediately in the event of a fire involving this substance. Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Vapors or gases

may travel considerable distances to ignition source and flash back.

Special protective equipment for firefighters **Further Information**

Use personal protective equipment. Wear neoprene gloves during cleaning up work after a fire. Exposure to decompositon products may be a hazard to health. Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment. Cool containers/tanks with water spray.

Section 6. Accidental Release Measures

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections

before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE

EQUIPMENT during clean-up.

Evacuate personnel to safe areas. Ventilate the area. Refer to protective Safeguards (Personnel)

measures listed in sections 7 and 8.

If this product is spilled and not recovered, or is recovered as a waste for Spill Clean-up

treatment and disposal, the CERCLA Reportable Quantity is 100 lbs. (release of an Unlisted Hazardous Waste with the Characteristic of Ignitability). Evaporates. Ventilate area using forced ventilation, especially low or enclosed places where

heavy vapors might collect.

Accidental Release Measures

Wear self-contained breathing apparatus (SCBA).

Section 7. Handling and Storage

Handling (Personnel) Avoid breathing vapors or mist. Avoid contact with skin, eyes and clothing.

> Provide sufficient air exchange and/or exhaust in work rooms. For personal protection see section 8. Handle in accordance with good industrial hygiene and

safety practice.

Handling (Physical Aspects) Vapors are heavier than air and may spread along floors. Vapors may form

> flammable mixture with air. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropirate standard. No sparking tools should be used. Take measures to prevent the build up of electrostatic charge. Keep away from open flames, hot surfaces and sources of ignition. When using DO NOT SMOKE. Do not use in areas where vapors may accumulate such as

paper shredders.

Dust Explosion class

Storage

Not applicable

Keep container tightly closed and in a dry, well-ventilated location. Store in original container. The product has an indefinite shelf life when stored properly.

Storage Period Recommended shelf life - 10 years provided product is stored in a dry location

as directed.

Storage Temperature Do not expose to temperatures above 120 degrees F (49 degrees C) as

overheating could cause can to burst. DO NOT leave in direct sunlight or

enclosed vehicle.

Section 8. Exposure Controls/Personal Protection

| Occupational Exposure Limits | Ingredient Name | ACGIH TLV | OSHA PEL | STEL | | |
|-----------------------------------|--|-----------|----------|------|--|--|
| | Ethane, 1,1-difluoro- | N/A | N/A | N/A | | |
| Personal Protective Equipment | N/A | | | | | |
| Engineering controls | Ensure adequate ventilation, especially in confined areas. Use respiratory protection if needed. | | | | | |
| Eye/Face Protection | wear safety glasses with side shields. Direct contact with liquid may cause frostbite. | | | | | |
| Respiratory Protection | For rescue use self-contained breathing apparatus. Vapors are heavier than air and can cause suffication by reducing oxygen available for breathing. | | | | | |
| Skin and body protection | As required by employer code. If there is risk of skin contact, wear protective clothing, gloves, etc. Direct contact with liquid can cause frostbite. | | | | | |
| General Hygiene Considerations | Handle in accordance with good industrial hygiene and safety practices. | | | | | |

Section 9. Physical and Chemical Properties

| Physical State | Gas |
|---------------------------------------|------------------------------|
| Color | Clear |
| Odor | slight, ether- like |
| Odor Threshold | No applicable data available |
| Solubility | Water - Slightly |
| Partition coefficient Water/n-octanol | N/A |
| VOC% | N/A |
| Viscosity | No applicable data available |
| Specific Gravity | 0.91 |
| Density lbs/Gal | 0.9 |
| Pounds per Cubic Foot | N/A |
| Flash Point | <-58°F (<-50° C) |
| FP Method | N/A |
| Ph | Neutral |
| Melting Point | No applicable data available |
| Boiling Point | -13 °F (-25 ° C) |
| Boiling Range | N/A |
| LEL | 3.9 |
| UEL | 16.9 |
| Evaporation Rate | No applicable data available |
| Flammability | Flammable |
| Decomposition Temperature | N/A |
| Auto-ignition Temperature | No applicable data available |
| Vapor Pressure | 5,960 KPa at 77F (25C) |
| Vapor Density | 2.4 at 77F (25C) (Air=1) |

Section 10. Stability and Reactivity

Reactivity Stable under recommended storage conditions.

Chemical Stability The product is chemically stable under recommended storage conditions.

Conditions to Avoid Aerosol containers are unstable at temperatures above 120 degrees F/49

degrees C

Incompatible Materials Incompatible products include Alkali metals, Alkaline earth metals, powdered

metals, powdered metal salts.

Hazardous Decomposition

Products

Decomposition products are hazardous. This material can be decomposed by high temperatures (open flames, glowing metal surfaces, etc.) forming

hydrofluoric acid and possibly carbonyl fluoride.

Section 11. Toxicological Information

Component Analysis - LC50 1,1-Difluoroethane - > 64000 ppm rat Component analysis - Oral 1,1-Difluoroethane - 1500 mg/kg rat

LD50

Effects of Acute Exposure - Contact with liquid may cause frostbite

Eye

Effects of Acute Exposure - Contact with liquid may cause frostbite

Skin

Effects of Acute Exposure - Excessive intentional inhalation may cause respiratory tract irritation and central

nervous system effect (headaches, dizziness). Vapors may cause dizziness or

suffocation.

Effects of Acute Exposure -

Ingestion

Inhalation

Not a normal route of exposure

Sensitization Non-hazardous by WHMIS/OSHA criteria.

Carcinogenicity Not classifiable as a human carcinogen. Animal testing did not show

carcinogenic effects. None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA

as a carcinogen.

Mutagenicity Animal testing did not show any mutagenic effects. Did not cause genetic

damage in cultured bacterial cells. Tests on mammalian cell cultures showed

mutagenic effects.

Reproductive Toxicity

No toxcicity to reproduction. Animal testing showed no reproductive toxicity. Animal testing showed no developmental toxicity.

Teratogenicity
Further Information

Cardiac sensitization threshold limit: 405000 mg/m3

Section 12. Ecological Information

Aquatic Toxicity 1,1-Difluoroethane 96 h LC50: Fish 295.78 mg/l 96 h EC50: Algae 47.76 mg/l

48 h EC50: Daphnia (water flea) 146.7 mg/l

Section 13. Disposal

Waste Disposal Methods Comply with applicable Federal, State/Provincial and Local Regulations. May be

a RCRA Hazardous waste due to the ignitability characteristic. Do not puncture

or incinerate container.

Contaminated Packaging Not Available

Section 14. Transport Information

UN Number 1030

UN Proper Shipping Name 1,1-Difluoroethane

DOT Classification 2.1 Packing Group

Packaging Exceptions Note: Falcon Safety Products has been granted a DOT special permit. A copy of

DOT Special Permit SP-11516 can be obtained by calling Falcon Safety

Products, Inc. at 908-707-4900.

Goods (TDG - Canada)

Transportation of Dangerous Proper Shipping name: 1,1-Difluoroethane Hazard Class: 2.1 UN number: 1030

Packaging Exceptions: Limited quantity (containers up to 125mL)

Proper Shipping Name: 1.1-Difuoroethane, Hazard Class: 2.1, UN Number: IATA/ICAO (Air)

> 1030. Maximum Net Quantity Packaging: Cargo Aircraft only - 150 kg maximum (forbidden on passenger aircraft). Maximum Net Quantity packaging cargo only:

150 kg.

Proper Shipping Name: 1,1-DIFLUOROETHANE. Hazard Class: 2.1. UN IMDG (Marine Transport)

Number: 1030.

Additional Information TDG Canada: Falcon Safety Products has been granted Equivalency Certificate

SU 9211 (ren. 1) by the TCSS, TDGD to offer for transport by road, rail and

marine.

Section 15. Regulatory Information

Canadian Federal This product has been classified in accordance with the hazard criteria of the Regulations

Controlled Products Regulations and the SDS contains all the information

required by the Controlled Products Regulations.

WHMIS Status

WHMIS Classification Class A - Compressed Gas, Class B - Division 1 - Flammable Gas

On the inventory, or in compliance with the inventory. **TSCA**

SARA 313 Regulated This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by Chemical(s)

SARA Title III, Section 313.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard **US Federal Regulations**

Communication Standard, 29 CFR 1910.1200.

Chemical(s)

NJ Right to Know Regulated Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances identified as carcinogens,

mutagens or teratogens): 1,1-Difluoroethane.

This product does not contain a chemical known to the State of California to California Prop. 65

cause cancer, birth defects or other reproductive harm.

Canada Domestic

This product is listed on the DSL inventory list and complies with the inventory

requirements administered by the governing country. Substances List (DSL)

Section 16. Other Information

Revision Date 2/17/2017

Disclaimer Information contained herein was obtained from sources considered technically

accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any

information contained in this document.

Prepared By Falcon Safety Products, Inc. 908-707-4900