

2MP HD-TVI IR Bullet Camera with Junction Box

VLB9

2.8mm fixed lens, white housing

Features

- Supports up to 2MP @ 30fps
- Full HD resolution over coax
- Supports HD-TVI, CVI, AHD. and 960H Analog
- IR Range: 65' (depending on scene reflection)
- 12VDC Operation (power supply not included)
- IP67 compliant, weather resistant
- Junction box included
- 5 year warranty













Camera Specifications

Image Sensor 1/2.9" CMOS, 2MP

Minimum Illumination 0 lux (IR ON)

Image Size 1920 x 1080

Video Output AHD/TVI/CVI/CVBS

Image System PAL/NTSC

Auto: 1/50s ~ 1/100000s (PAL); **Electronic Shutter** 1/60s ~ 1/100000s (NTSC)

IR Distance 32.8ft ~ 65.6ft

Frame Rate 30fps (60Hz); 25fps (50Hz)

Lens Mount M12

S/N Ratio ≥ 52dB (AGC OFF)

Functions

Defect Correction

Function Control OSD (COC Control)

Day & Night Yes, Smart IR

Digital WDR Yes

DNR 3D DNR

AGC Yes

Auto White Balance Yes

Compensation BLC

Front Light Compensation Yes

Sharpness Yes

Mirror Yes

Image Setting Yes

Pan (0° ~ 360°); Til (0° ~ 80°); Angle Adjustment

Rotation (0° ~ 360°)

Operating & Unit Specifications

Power 12VDC (power supply not included)

IR OFF: < 1W: IR ON: < 3W Power Consumption

Operating Temperature -22°F ~ 122°F

Operating Humidity 10% ~ 95% RH

Unit Dimensions 6.59" (L) x 2.93" (W) x 2.93" (H)

Unit Weight .82 lbs.







FMT1



TVIUTPPT HD Video Transceiver with Pigtail



O5VLWMJ



TVIUTP over UTP











CLTX1 Ceiling Mount 4" Extension



*Products are in compliance with NDAA Section 889 Part B Guidelines





Auto