



Pacer



Marine Battery Cable

Pacer's Marine battery cable is designed with the harshest marine environments in mind. To survive in a marine environment, battery cable needs to be able to survive a wide range of environmental conditions. This cable is designed for durability, flexibility, and longevity. Our marine battery cable is so durable in fact, that it is designed to out-live the battery itself.



Construction

Type III Class K annealed fine stranded tinned copper








Compliances

-  UL Standard 1426 BC-5W2
-  CSA: TEW
-  Machine Tool Wire
-  ABYC: E-11.16
-  Coast Guard: 33 CFR part 183
-  AWM 1232/1283

Pacer is a Proud Member of:



Resistances

-  Acid Resistant
-  Alkali Resistant
-  Oil Resistant
-  Moisture Resistant
-  Abrasion Resistant
-  Gasoline Resistant
-  Flame Resistant



GAUGE SIZE	CONDUCTOR STRANDING	NOM. INSULATION (IN.)	NOM. O.D. (IN.)	NOM. CIRCULAR MILS	NOM. MM ²	APPRX LB/M
6	7x38/0.0100	0.060	0.350	26600	13.5	136
4	7x60/0.0100	0.060	0.400	42000	21.3	189
2	7x95/0.0100	0.060	0.465	66500	33.7	292
1	19x44/0.0100	0.080	0.550	83600	42.4	360
1/0	19x56/0.0100	0.080	0.600	106400	53.9	450
2/0	19x70/0.0100	0.080	0.650	133000	67.4	551
3/0	19x88/0.0100	0.080	0.705	167200	84.7	670
4/0	19x111/0.0100	0.080	0.780	210900	106.9	820

Built for durability, flexibility, and longevity in the harshest marine environments

So flexible that you can tie it into a knot without compromising any of its qualities

Proprietary insulation ensures the highest level of protection available

Ease of installation and the longevity of its design have helped solidify this battery cable as the choice of boating professionals



Color Options for Marine Battery Cable

	Black	Red	Orange	Yellow	Green	White
WUL6						
WUL4						
WUL2						
WUL1						
WUL1/0						
WUL2/0						
WUL3/0						
WUL4/0						