

PE 901 UV-RESISTANT MARINE HULL PRESERVATION TAPE

TYPICAL APPLICATIONS

- Used for protection during marine transportation and temporary outdoor boat storage
- For use in seaming and sealing applications across a variety of surfaces
- May be used on surfaces that are gel-coated

PRODUCT FEATURES

- UV-resistant polyethylene film tape
- Excellent conformability and flexibility
- Clean removal*
- Maintains a watertight seal
- *Although hull preservation tape is designed to not leave residue, we recommend testing a small area before applying to the entire surface to avoid the possibility of a top layer of paint or finish removal

CONSTRUCTION

Backing: Polyethylene film

Adhesive: Synthetic rubber adhesive

STANDARD WIDTHS

1.88 in; 2.83 in; 3.77 in
48 mm; 72 mm; 96 mm

STANDARD LENGTH

36.1 yd
33 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in


APPLICABLE STANDARDS

UL 723
ASTM e84
ASTM D-3833

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLORS



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Backing	35 oz/in width	3.8 N/10 mm
Adhesion to Stainless Steel	85 oz/in width	9.3 N/10 mm
Application Temperature Range	65 F to NA	18 C to NA
Elongation	100%	100%
Service Temperature Range	14 F to 158 F	-10 C to 70 C
Tensile	22 lbs/in width	38.5 N/10 mm
Thickness	9.0 mils	0.23 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

