

## PE 900 UV-RESISTANT MARINE HEAT SHRINK TAPE

### TYPICAL APPLICATIONS

- Used for marine shrink applications and vapor barrier seaming in boat storage and transportation applications
- Also used for patching, repairing, bundling, wrapping and sealing applications across a variety of surfaces

### PRODUCT FEATURES

- UV-resistant polyethylene film tape
- Excellent conformability and flexibility
- Maintains a watertight seal

### CONSTRUCTION

Backing: Polyethylene film

Adhesive: Synthetic rubber adhesive

### STANDARD WIDTHS

1.88 in; 2.83 in; 3.77 in; 5.67 in  
48 mm; 72 mm; 96 mm; 144mm

### STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

UL 723

ASTM e84

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLORS



Blue  
(BLU)



White  
(WHI)

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Backing	35 oz/in width	3.8 N/10 mm
Adhesion to Stainless Steel	85 oz/in width	9.3 N/10 mm
Application Temperature Range	65 F to NA	18 C to NA
Elongation	100%	100%
Service Temperature Range	14 F to 158 F	-10 C to 70 C
Tensile	22 lbs/in width	38.5 N/10 mm
Thickness	9.0 mils	0.23 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

