



MARPOL*
International Convention for the Prevention of Pollution from Ships

HULL & BOTTOM CLEANER

NON-FUMING FORMULA SAFELY REMOVES:

- Barnacles • Zebra Mussels • Calcium • Lime • Hard Water Stains
- Mineral Deposits from Metal, Paint and Glass • Rust Stains



When used as directed, Hull & Bottom Cleaner safely and easily removes barnacles, scales, and rust. It is safe and effective for closed coil systems. Hull & Bottom Cleaner is an environmentally responsible MARPOL Annex V compliant product.

Ready to Use

READ INSTRUCTIONS PRIOR TO USE
KEEP OUT OF REACH OF CHILDREN
1 GALLON (3.78 L)



DITEC®
MARINE PRODUCTS



This product is not a marine pollutant and may be rinsed with fresh wash water into rivers, streams, and other waterways.

MARPOL*
COMPLIANT

Hull & Bottom Cleaner offers exceptional performance and cost efficiency.

- Less corrosive organic acid replacement to be used in place of highly corrosive mineral acids.
- Less corrosive than hydrochloric and other harmful acids.
- More effective than citric and glycolic acid.
- When used as directed, safe for painted and gelcoat surfaces.
- Contains non-corrosive inhibitors for most metals (not for use on or near aluminum, brass or soft and finished metals).
- This product is not a marine pollutant.

Directions For Use:

For best results, apply **Hull & Bottom Cleaner** and allow it to affect the surface for 30 seconds to 5 minutes. Brush the surface if needed. Rinse with fresh water. If the growth or stain is not completely removed, repeat the application. **Hull & Bottom Cleaner** must be rinsed off of the treated surface. If used around metal or delicate surfaces, thoroughly clean the surface with DiTEC Elite Boat Wash or Wipeout.

DiTEC believes that the environment is our most precious asset, and we must take personal responsibility for how we affect it. We develop products that are unsurpassed in quality and performance, and meet or exceed the highest environmental regulatory standards in the world. The DiTEC **Hull & Bottom Cleaner** achieved the requirements for Inherent Biodegradability by the OECD 306 standard for degradation within 60 days of the test time frame.

DiTEC Marine Products, LLC
W229 N2512 Duplainville Rd.
Waukesha, WI 53186 USA
Tel: 1-800-572-4390
ditecmarineproducts.com



First Aid

INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Call poison control or doctor if exposure occurs due to the severity of the chemical.

DiTEC Marine Products, LLC
W229 N2512 Duplainville Rd.
Waukesha, WI 53186 USA
Tel: 1-800-572-4390
ditecmarineproducts.com



*Not regulated according to MARPOL guidelines



DANGER:

May be corrosive to metals. Causes severe skin burns and eye damage. May cause respiratory irritation. May cause drowsiness or dizziness. **Wear protective gloves and clothing. Ensure proper eye and face protection.**

Wash hands and exposed areas after using. Wash any contaminated clothing before reuse. Keep chemical in its original container when not in use and dispose of in accordance with local and regional regulation.