



MARPOL*
COMPLIANT

ORGANIC ACID REPLACEMENT

TEAK CLEAN

ONE-STEP CLEANER AND BRIGHTENER



Teak Clean is exceptional for cleaning and brightening teak and other wood surfaces. It safely cleans and restores wood to its natural color. Teak Clean combines superior cleaning performance with exceptional environmental properties.

Ready to Use

READ INSTRUCTIONS PRIOR TO USE
KEEP OUT OF REACH OF CHILDREN
1 GALLON (3.78 L)



DITEC®
MARINE PRODUCTS



This product is not a marine pollutant and may be rinsed with fresh wash water into rivers, streams, and other waterways.

MARPOL*
COMPLIANT

DITEC TEAK CLEAN

Recommended Usage:

For use in well-ventilated and open areas and large decks.

Application:

Make sure to wear proper safety gear, including nitrile gloves. **For best results, apply DITEC Teak Clean to a dry or slightly damp surface. DO NOT SATURATE THE WOOD WITH WATER!**

1. Apply this product by pouring directly to the deck surface or applying with a chemical-resistant sprayer or pump sprayer.
2. Allow **Teak Clean** to soak/dwell on the surface for 30 seconds to 5 minutes. Water may be added to the surface at this point.
3. Brush the surface with a stiff deck cleaning brush or a polypropylene pad (3M medium blue Doodlebug pad or similar) in the same direction as the wood grain.
4. Frequently inspect and rinse your brush or scrubbing pad to remove embedded wood fibers. Continue this process until no wood fibers are embedded after scrubbing. This will ensure a high quality result. **THOROUGHLY** rinse the deck clean with fresh water, and repeat steps 1-3 if necessary.

WARNING: If **Teak Clean** contacts any metal, stone or delicate surfaces, the surfaces must be thoroughly washed with soap and water.

There are no GHS ratings that apply to this product at this time. This product is an acid replacement. It is acidic PH: <1.

DITEC believes that the environment is our most precious asset, and we must take personal responsibility for how we affect it. We develop products that are unsurpassed in quality and performance, and meet or exceed the highest environmental regulatory standards in the world. This product may be safely discharged into rivers, streams, oceans and other waterways.



First Aid

INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before re-use.

INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

DITEC Marine Products, LLC
W229 N2512 Duplainville Rd.
Waukesha, WI 53186 USA
Tel: 1-800-572-4390
ditecmarineproducts.com



*Non regulated according to MARPOL guidelines

