

TRITON^{2.0}

WORLD'S BEST TEAK PROTECTOR

Ultrazorb UV Protection



Triton 2.0 is the ultimate protection for teak and other wood surfaces. Triton 2.0 binds to the wood fibers and creates a protective, highly water and oil repellent surface. Triton 2.0 does not change the appearance, color or feel of the surface being treated.

One gallon treats up to 600 ft² (57 m²)

Ready to Use



DITEC[®]
MARINE PRODUCTS



READ INSTRUCTIONS PRIOR TO USE
KEEP OUT OF REACH OF CHILDREN
1 GALLON (3.78 L)

Triton 2.0 is the ultimate protection for teak and other wood surfaces in the marine environment. It offers water and oil repellency and helps prevent the growth of mold, mildew, and algae. The one-step application significantly reduces surface maintenance.

Before Application:

Thoroughly clean the wood surface prior to applying **Triton 2.0**. For teak that is slightly grayed or needs a light cleaning, use Teak Clean. For very dirty and heavily grayed teak, use Teak Magic Part 1 & 2. Allow the surface to completely dry.

Application:

Protect yourself: Use gloves and goggles. **Shake well before use.** Wood surface must be **COOL TO THE TOUCH AND COMPLETELY DRY** prior to application. For small areas, put **Triton 2.0** in a bucket and apply with a soft sponge, brush or roller. For large areas, apply **Triton 2.0** directly to surface with a soft sponge, brush, roller, or pump sprayer. For the most complete and even application, use a pump sprayer to apply, then back roll onto the surface. **For initial application, apply only two coats.** Additional coats will not improve protection. Dry time between coats is 40-60 minutes. **Wood surface must remain dry for 12 hours after application.** **Triton 2.0** is fully cured after 24 hours.

Dispose of contents/container in accordance with local/regional/national/international regulations.

DiTEC Marine Products, LLC
W229 N2512 Duplainville Rd.
Waukesha, WI 53186 USA
Tel: 1-800-572-4390
ditecmarineproducts.com



First Aid

INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.



DANGER:

Flammable liquid and vapor. May be fatal if swallowed and enters airways. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and clothing and eye and face protection. If swallowed: Immediately call a poison center or physician. If on skin (or hair): Take off all contaminated clothing immediately. Rinse skin with water. Do not induce vomiting. In case of fire: Use appropriate method to extinguish. Store in a well-ventilated place. Keep cool. Store locked up.