



Super Cut Compound (1674)

DESCRIPTION

MALCO® Marine Super Cut Compound is an ultra-aggressive compound designed to remove P800 and finer dual action or wet sand scratches and medium to light oxidation from gel coat, fiberglass and select painted surfaces.

DIRECTIONS

SHAKE WELL BEFORE USING. Do not apply in sunlight or on warm surfaces. Apply a 2" dab of Super Cut for a 2' x 2' (.6m x .6m) section and spread with the cutting pad. With a rotary buffer, buff at speed between 1600 to 2600 rpm. Recommended speed is 2200 rpm. Work the buffer side to side slowly in a figure eight pattern as you slowly buff the gel coat surface until most of the product is gone and gloss appears. Add more Super Cut and repeat if necessary to remove deep scratches. Remove compound splatter as soon as possible with a soft, clean damp cloth such as a microfiber cloth.

FEATURES & BENEFITS

Versatile formula

Safe for gelcoat, fiberglass and painted surfaces

Ultra aggressive compound

Removes P800 and finer dual action or wet sand scratches and light to medium oxidation

VOC Compliant

Can be sold in 50 states

Water based formula

Environmentally friendly, easy to use

PACKAGE SIZES

12 - 1 Quart

Part number: 167432

4 - 1 Gallon

Part number: 167401



FREQUENTLY ASKED QUESTIONS

PRODUCT FAQ'S:

Q1: Is Super Cut Compound paint shop safe?

A1: Super Cut Compound is paint shop safe and contains no silicone, wax, or fillers.

Q2: What grit sand scratches will Super Cut Compound remove?

A2: Super Cut Compound is designed to remove P800 or finer sand scratches.

Q3: What is the main use for Super Cut Compound?

A3: Super Cut Compound is a very versatile product that works well to remove aggressive sand scratches and defects in automotive and marine applications.

Q4: Can Super Cut Compound be used with other Malco buffing systems?

A4: Yes, Super Cut Compound is compatible with all Malco buffing products and systems.

Q5: How do I know what Malco pad to use with Super Cut Compound?

A5: For best results use the white, hook and loop 100% twisted wool pad from Malco (single sided - #890141, double sided - #810073).