



ShieldPro

UV Creme Wax (1661)

DESCRIPTION

MALCO[®] Marine Crème Wax UV provides long lasting shine and UV protection on fiberglass, gelcoat and painted marine finishes in one easy step. Advanced technology polishing agents and waxes combine with aminofunctional silicones, dual functional UV absorber, silicone resin and polymers to create unbeatable gloss and exceptional protection against salt, corrosion, and the sun's ultraviolet rays.

DIRECTIONS

Before applying, wash boat thoroughly with Hydrofoam Concentrated Boat Wash (1620) to remove heavy accumulations of dirt and grime. Make sure surface is cool and dry prior to application. Shake well before using. Apply ShieldPro UV to the surface using a soft cloth or wax applicator pad and spread wax to a thin, even film. Apply to one section at time or to the entire surface. Allow wax to dry to a light haze and polish off either by hand with a soft, clean microfiber cloth or with a random orbital polisher.

FEATURES & BENEFITS

Versatile formula

Protects gel coat, fiberglass, and painted surfaces.

• Provides long lasting shine and UV protection on fiberglass, gelcoat and painted marine finishes in one easy step.

• Advanced technology polishing agents and waxes combine with aminofunctional silicones, dual functional UV absorber, silicone resin and polymers to create unbeatable gloss and exceptional protection against salt, corrosion, and the sun's ultraviolet rays.

Easy to use

Can be applied by hand or using a DA machine or buffer.

PACKAGE SIZES

12 – 16 oz.

Part number: 166132

4 – 1 Gallon

Part number: 166101



FREQUENTLY ASKED QUESTIONS

Q1: What is the main use for ShieldPro?

A1: ShieldPro protects against salt, oxidation and the sun's UV rays.

Q2: What preparation is needed before applying ShieldPro?

A2: Wash boat or RV thoroughly with Hydrofoam Concentrated Boat Wash (1620) to remove heavy accumulations of dirt and grime. Make sure the surface is cool and dry prior to application.

Q3: How do you apply ShieldPro?

A3: Apply ShieldPro to the surface using a soft cloth or wax applicator pad and spread wax to a thin, even film. Apply to one section at time or to the entire surface. Allow wax to dry to a light haze and polish off either by hand with a soft, clean microfiber cloth or with a random orbital polisher. When using with a DA buffer, use with Malco DA pad (890172). When using with a rotary buffer, use Malco rotary pad (890144).

Q4: How long does ShieldPro protect the surface of the boat or RV?

A4: ShieldPro will protect the vehicle surface for up to 6 months.

Q5: Can ShieldPro be used on freshly painted surfaces?

A5: No, ShieldPro should only be used on fully cured painted surfaces. Check with the paint manufacturer for full cure time before applying ShieldPro.