



MaxProduction Compound (1650)

DESCRIPTION

MALCO® Marine MaxProduction is an innovative compound that provides aggressive cutting action for heavy scratch removal and produces a gloss final finish. This water-based, easy-to cleanup formula is designed to remove P600 and finer sand scratches on gel coat and other solid surfaces in marine and industrial applications. Significantly reduces sanding and buffering time without the use of waxes, silicones, or fillers.

DIRECTIONS

Shake well before using. For best results on P600 or finer grit sand scratches, use with a Malco black & white wool buffering pad (#890146). Surface should be clean, cool and dry. Apply compound to the pad. Buff with a seasoned pad at speeds between 1400 - 2200 rpm. For best results, recommended buffering speed is 1800 rpm. Work the buffer slowly from left to right and front to back using light to medium surface pressure. Slowly reduce buffer surface pressure as product diminishes and gloss appears. Repeat as necessary until sand scratches disappear. Wipe surface with a clean microfiber cloth. Follow with MaxFinishing Polish (#163501) for a high-gloss, swirl-free final finish on darker surfaces.

FEATURES & BENEFITS

Innovative and versatile compound

Removes P600 and finer sand scratches and provides a final gloss finish with one product

Works on tooling gels, solid surfaces and production gel coats

Reduces the number of products needed

Water-based formula

Environmentally friendly, safe to use

PACKAGE SIZES

4 – 1 Gallon

Part number: 165001



FREQUENTLY ASKED QUESTIONS

PRODUCT FAQ'S:

Q1: What grit sand scratches will MaxProduction Compound remove?

A1: MaxProduction Compound is designed to remove P600 or finer sand scratches.

Q2: What is the main use for MaxProduction Compound?

A2: MaxProduction Compound is a very versatile product that works well to remove aggressive sand scratches, defects, and heavy oxidation in marine applications.

Q3: Can MaxProduction Compound be used with other Malco buffering systems?

A3: Yes, MaxProduction Compound is compatible with all Malco buffering products and systems.

Q4: How do I know what Malco pad to use with MaxProduction Compound?

A4: For best results use the black and white, wool buffering pad from Malco (#890146).

Q5: What is the difference between MaxProduction and SuperCut Compounds?

A5. MaxProduction is a newer version of SuperCut Compound. MaxProduction uses a different abrasives which feels less gritty to the touch. However, it provides a much higher, more efficient cut for production fiberglass and tooling molds.