by Xanigo Marine

TECHNICAL DATASHEET

XMZ50 | BLACK

MODULAR WIRE & CABLE MANAGEMENT

ZipStiks provides a continuous support platform for organized wire and cable routing. Connecting strips and break-apart segments allow custom layouts for boat manufacturing, repair, and maintenance.

PRODUCT SPECIFICATIONS

Material	Nylon 6/6 with UV protection
Overall dimensions (L × W × H)	11 × 0.625 × 0.394 in
Configuration	11 break-apart segments per strip
Zip-tie slots	Small: 0.196 in	Large: 0.319 in
Mounting holes	Designed to create a flush mount with a #8 stainless steel flathead screw.
Recommended screw quantity	Three screws per full-length strip
Attachment methods	Screws or recommended adhesive
Color / SKU	Black / XMZ50
Packaging	50 strips/box; 10 boxes/case (500 strips)

RECOMMENDED ADHESIVES

Recommendation basis: achieved over 250 lb in pull testing on unprepared fiberglass.

Bostik Pliogrip 7773	288.8 lb
Permabond TA4550	276 lb
Plexus MA300	268 lb

Pliogrip 7773: fast cure time and strength. Follow adhesive manufacturer instructions for best results. Reported pull-test results are not a working-load rating.

Additional adhesives are currently undergoing laboratory testing.
More recommendations coming soon.

Installation: Connect strips or break apart to suit the route. Leave space between sections at bends. Select the appropriate zip-tie track and follow adhesive instructions for preparation and curing.