



Feature / Specification	SINGLE COLOR THRU-HULL				
	THX301	TIX301	THX601	TIX601	THX1201
Fixture Lumens	4,670	4,670	9,790	9,790	16,010
Available Colors	White, Blue or Green				
Color Change	No. See Color-Change Models				
Color Cycle	No. See Color-Change Models				
Timed Color Cycle	No. See Color-Change Models				
Fishing Strobe Mode	No. See Color-Change Models				
Beam Angle	110°				
LED Power-HICOB Array:	Yes				
Typical LED Life	50,000+ hours				
Voltage Range	9-31 Volts	9-31 Volts	9-31 Volts	9-31 Volts	20-31 Volts
Max Current Draw 12 / 24VDC	3.75 / 1.8A		7.5 / 3.75A	7.5 / 3.75A	NA / 6.25A
Housing Type	Aluminum Bronze	Interchangeable Aluminum Bronze	Aluminum Bronze	Interchangeable Aluminum Bronze	Aluminum Bronze
ATRB (Automatic Thermal Roll-Back)	Yes	Yes	Yes	Yes	Yes
Low Voltage and Diagnostics	Yes. In-built driver LED indicators				
Voltage and Thermal Protection	Yes				
"Soft-Start" Electronics Protection	Yes, on start-up				
Reverse Polarity Protection	Yes				
Light Face Diameter	2.5"	3.5"	3.25"	5.0"	4.25"
Profile (height) of housing	0.40"	0.20"	1.25"	0.33"	1.25"
Hole cut-out for shaft & cable	1.0"	2"	1.0"	3.5"	1.0"
Shaft length	4.9"	2.9"	4.9"	4.5"	4.9"
Light cable	6.5 ft. w/ waterproof connector. Plugs into Driver (except TIX301)				
Driver	External	Internal	External	External	External