

Scobra®

CLASS-D FIXED MOUNT VHF RADIO

The latest in Class-D Digital Selective Calling (DSC) Technology.

Submersible Designed to IPX8 (JIS8) standards.

Rewind-Say-Again® Replay missed VHF calls. Automatically records the last 20 seconds with a digital voice recorder.

PA Output PA function for public address to external speaker.

Softkey Operation Easily make calls, activate advance features and navigate through menus.

Radio Check

Checks battery voltage when transmitting, RF power output, and antenna output.

Flush mount kit included

Everything you need for quick and easy install.








MR F57W E

| Features | Benefits |
|---|---|
| DSC (Digital Selective Calling) | Compliant with the latest specifications for Class-D VHF Radios. Digital Selective Calling allows you to send a distress signal at the touch of a button or exchange position information with other boats or stations. DSC features on this Class-D radio include; A Dedicated Channel 70 (DSC Channel) Receiver, GPS Position Display Capability, Illuminated Distress Button, Easy MMSI Entry, Position Send and Request, Position Input Reminder, Coast Guard DSC Check Capability, etc. |
| 1 or 25 Watts | Dual output power for short and long communication. |
| International, U.S.A. & Canada Channels | Allows operation on any of the three (3) different channel maps established for these areas. |
| Rewind-Say-Again® | Replay missed calls. Automatically records the last 20 seconds of incoming radio transmissions. Handy when in noisy conditions. |
| Radio Check | Checks battery voltage when transmitting, RF power output, and antenna output. |
| Instant Channel 16 | Instant access to channel 16 for emergency situations. |
| GPS Capability | Plug-and-Play using the new C.P.S. (Cobra Positioning Systems) external GPS. No other connections required. You can send your position information in case of emergency, or exchange position information with other boats. |
| Dual Watch | Monitors two (2) channels at once - Channel 16 and one (1) user selected channel. |
| Scan / Memory Scan | Scan all channels to find conversations in progress, or scan channels placed into memory. |
| Channel Names | Friendly VHF channel names under the channel number. |
| Signal Strength Meter | Shows the strength of incoming signal. |
| Illuminated Keys | Allows high visibility of keys. |
| Illuminated LCD Display: Large | Allows high visibility of display. |
| Noise Canceling Microphone | Blocks background noise. |
| External Speaker and PA Speaker | Connect an external speaker and a PA (Public Address) speaker. |
| NMEA In and Out | NMEA in for GPS input. NMEA output to display other vessels and their information transmitted by DSC on your chartplotter. |
| Submersible | Meets JIS8/IPX8 standards; Submersible for 30 minutes in 1.5 meter deep water. |
| External Alarm Input | Senses the alarm from your chartplotter and uses the speaker on the radio to amplify the alarm for waypoint arrival, MOB, etc. |
| ATIS | Capable of operating within the Automatic Transponder Identification System. ATIS includes data at the end of a transmission for station identification. |

Included Accessories

Flush & Surface Mount KitEasy installation of radio in or on almost any flat surface.GPS Interface CableAllows connection of a GPS receiver or NMEA 0183 devices.





Unit Specifications General

| Number of Channels | All: International, U.S.A. & Canadian Channels |
|----------------------------|---|
| Channel Spacing | 25 kHZ |
| Modulation | 5 kHz Max. |
| Input Voltage | 13.8 VDC |
| Current Drain: Stand-by | 200 mA |
| Receive | 300 mA |
| Transmit | 5 A @ High Power 1 A @ Low Power |
| Temperature Range | -20°C to 60°C |
| Unit Dimensions | 6.25" x 2.25" x 7.125" (159 mm x 57 mm x 180 mm) |
| Unit Weight (Lbs) | 2 lbs., 6.8 oz. (1100 g) |

Receiver

| Frequency Range | 156.050 to 163.275 MHz |
|--------------------------------|---------------------------------------|
| Receiver Type | Double Conversion Super-Heterodyne |
| Sensitivity: 20 dB Quieting | 0.35 uV |
| 12 dB Sinad | 0.30 uV |
| AF Output | 4 Watts @ 8 Ohms |

Transmitter

| Frequency Range | 156.025 to 157.425 MHz |
|----------------------|---|
| RF Output Power | 1 or 25 Watts |
| Spurious Emissions | -75 dB @ High Power -72 dB @ Low Power |
| Microphone Type | Electret |
| Microphone Impedance | 2000 Ohms |
| Frequency Stability | +/-10 ppm |
| FM Hum & Noise | 50 dB |
| | |

Packaging Specifications

| a sing op o | |
|-----------------------------------|----------------------------|
| Individual Clam/Box Dimensions | 3.25"H x 12.60"W x 9.70" D |
| Individual Clam/Box Weight | 3.7 lbs. |
| Master Pack Qty. | 2 |
| Master Pack Dimensions | 9.80"H x 13.80"W x 8.10"D |
| Master Pack Weight | 9.40 lbs. |
| SKU # (White) | MR F57W E |
| UPC # | 0 28377 20182 0 |
| Master Pack Barcode | 5 0028377 20182 5 |
| SKU # (Black) | MR F57B E |
| UPC # | 0 28377 20189 9 |
| Master Pack Barcode | 5 0028377 20189 4 |

Specifications subject to change without notice.

©2015 Cobra Electronics Europe Limited, Dungar House,

Northumberland Avenue, Dun Laoghaire, County Dublin, Ireland

Cobra®, Nothing Comes Close to a Cobra® and the snake design are registered trademarks of Cobra Electronics Corporation, USA.

Cobra Electronics Corporation ${}^{\rm T\!M}$ is a trademark of Cobra Electronics Corporation, USA.

CEEL[™] is a trademark of Cobra Electronics Europe LTD.

