

## Desktop Switching Power Supply

Model  
SEC-1212  
10 Amps



### Design Features

- Advanced switch-mode technology
- Reliable power with minimum weight and size
- Circuit innovations minimize output voltage ripple and RFI
- Input voltage can be set at 120 VAC or 240 VAC
- UL listed to both USA & Canadian safety standards

**3 YEAR LIMITED WARRANTY**



MODEL NO.	SEC-1212
INPUT VOLTAGE (NOMINAL)	120 VAC, 60 Hz
OUTPUT VOLTAGE	13.8 VDC
OUTPUT RIPPLE & NOISE (ON FULL LOAD, PEAK TO PEAK)	150 mV
OUTPUT CURRENT, CONTINUOUS	10 A
CURRENT LIMIT	14 A
COOLING	Convection cooled
PROTECTIONS	Over current, short circuit and over voltage (Through PWM Controller)
ENVIRONMENTAL TEMPERATURE RANGE	0 - 30°C
AC INPUT	Detachable power cord C/W NEMA 5-15P plug
DC OUTPUT	Terminals with tubular hole DIA. 0.2" (5 mm) with set screw
FUSE RATING	5 mm x 20 mm Glass fuse, 125 V or 250 V (Time delay / slow blow), 3 A
BUSSMANN	GDC-3
LITTELFUSE	239003
DIMENSIONS, MM (W x D x H)	185 x 208 x 59.5
DIMENSIONS, INCHES (W x D x H)	7.28 x 8.19 x 2.34
WEIGHT, KG	1.36
WEIGHT, LB	3
SAFETY CERTIFICATION	cUL <sub>USA</sub> Listed, UL60950-1, E179076
EMC CONFORMITY	FCC Part 15(B), Class B Digital Device

NOTE: Specifications are subject to change without notice