

MODEL OVERVIEW



Model	SC30B20-9	R12i20-9	XC20B20-9	XC20i20-9	SW16B37-9	SW16i37-9
Image Specs						
Megapixels	30	12	20	20	16	16
Trigger Speed	> ½ Sec	> ½ Sec	> ½ Sec	> ½ Sec	> ½ Sec	> ½ Sec
Illumination Range	110 Feet	80 Feet	95 Feet	100 Feet	80 Feet	85 Feet
4:6 Standard	X	X	X	X	X	X
16:9 Wide Angle	X	X	X	X	X	X
Color Daytime Images	X	X	X	X	X	X
B/W Night Images			X	X	X	X
Video Specs						
Video Resolution	720p / 1080p HD	720p HD	720p HD	720p HD	720p HD	720p HD
Video Duration	15 Sec	15 Sec	5 / 15 / 30 Sec	5 / 15 / 30 Sec	5 / 15 / 30 Sec	5 / 15 / 30 Sec
Color Daytime Video	X	X	X	X	X	X
B/W Night Video	X	X	X	X	X	X
Environmental Data						
Tune & Date Stamp	X	X	X	X		
Location Stamp	X	X	X	X	X	X
Moon Phase Stamp	X	X	X	X	X	X
Technology						
Adaptive Illumination	X		X	X	X	X
Exposure Control	X	X	X	X	X	X
Lightsout™	X		X		X	
Silent Shield™	X		X	X	X	X
True-Dual Cam™	X		X	X		
Zero Detection	X		X	X	X	X
Hardware						
Emitter Count	42 Invisible Black LEDs	36 Infrared LEDs	42 Invisible Black LEDs	42 Infrared LEDs	42 Invisible Black LEDs	36 Infrared LEDs
Finish	Trubark™	Trubark™	Trubark™	Trubark™	Trubark HD™	Trubark HD™
Attachment	Adjustable Strap	Adjustable Strap, T-Post Bracket	Adjustable Strap	Adjustable Strap	Adjustable Strap, Magnetic Ball Bracket	Adjustable Strap, Magnetic Ball Bracket
Power Source	8 AA Batteries	8 AA Batteries	8 AA Batteries	8 AA Batteries	4 AA Batteries	4 AA Batteries

