


## U-bolt pad eye - Dia: 4 mm - Length: 50 mm

Part #6511




### Description

Fully dropforged product with high quality stainless steel  
Outstanding working and breaking loads  
For any kind of fastening applications (shrouds, lifelines, blocks...)  
Delivered with bolts and counterplate  
Max tightening torque : 2.3 Nm

### Applications

Various fastening applications: shrouds, lifelines, blocks...

## Technical information

|   |                            |
|---|----------------------------|
| Materials   | 316L stainless steel grade |
| Length (mm)   | 50                         |
|  Working load (kg) | 480                        |
| Breaking load (kg)  | 1000                       |
| Weight (g)  | 22                         |
| A (mm)  | 24                         |
| B (mm)  | 21                         |
| C (mm)  | 27                         |
| D diameter (mm)   | 4                          |
| L (mm)  | 50                         |

### Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.  
The safety factor is 5 times the breaking load.  
 $WLL = \text{Breaking load} / 5$

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.