## Lock N' Stow

- Locks outboard motor in forward position while trailering, greatly reducing the damaging effects of road shock
- Doesn't tie engine's lower-unit to trailer, eliminating excessive pressure on hydraulic seals and scuff marks
- Small compact mount can be easily stored in just about any boat compartment
- · Constructed of black powder-coated steel with stainless steel pins

Fits:	OEM Part #	Part #
OMC, Bombardier 1989 to present, 100HP and up	_	10309
Mercury engines 200 OpitMax, 255 OptiMax, 225HP EFI, 250HP EFI	_	10107
Mercury engines 135 OptiMax, 150 OptiMax 175 OptiMax, 75HP-200HP EFI	_	10108



## **Tie-Down Straps**

## **Quick-Release Transom Tie-Down Straps**

When properly secured to transom eyes and trailer, transom straps reduces vertical and lateral movement to safely secure the boat to the trailer. They also reduce bouncing of the boat on the trailer pads or rollers. Available in 2 inch width for larger trailerable boats and 1 inch width for lighter boats.

Webbing: Strong webbing. Resists rot, oils, gasoline, and most chemicals.

**Buckle:** Quick-Release (Over-Center) buckle. Strong and secure, yet easy to use. Quicktightening. Cinch tight and secure by depressing buckle handle. Release by lifting the buckle handle.

**Hook:** Vinyl-Coated S-Hook to prevent scratching boat or trailer finish. Corrosion-resistant. Heavy-gauge.

**Special Features:** Protective pad behind buckle to prevent marring and scratches on gel coat and painted surfaces. Hook-N-Loop closure secures the buckle handle in the locked position.

Description	Width	Length	OEM Part #	Part #
One pair	2"	4 ft.	_	15232-7

## **Quick-Release Gunwale Straps**

Gunwale straps secure the entire aft section of the boat over the gunwale to the trailer and restrict vertical movement while on the road.

Webbing: Strong webbing. Resists rot, oils, gasoline, and most chemicals.

Buckle: Quick-Release (Over-Center) buckle. Strong and secure, yet easy to use.

Quick tightening. Cinch tight and secure by depressing buckle handle. Release by lifting the buckle handle.

**Hook:** J-Hook with snap-closure for secure, easy attachment. Electrostatic Discharge Coating (EDC) finish to prevent corrosion. Heavy gauge.

Description	Length	OEM Part #	Part #
2" Wide	13 ft.	_	15221-7



